

Eastman(TM) MAK

Version 2.3 PRD Revision Date: 07/27/2018 SDS Number: 150000001054 SDSUS / Z8 / 0001 Date of last issue: 06/21/2017 Date of first issue: 09/06/2016

SECTION 1. IDENTIFICATION

Product name : Eastman(TM) MAK
Product code : 00133-00, P0013300, P0013301, P0013305, P0013309, P0013310, P0013311, P00133K0, E0013301, P0013312

Manufacturer or supplier's details

Company name of supplier : Eastman Chemical Company
Address : 200 South Wilcox Drive
Kingsport TN 37660-5280
Telephone : (423) 229-2000
Emergency telephone : CHEMTREC: +1-800-424-9300, +1-703-527-3887 CCN7321

Recommended use of the chemical and restrictions on use

Recommended use : Solvent
Restrictions on use : None known.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3
Acute toxicity (Oral) : Category 4
Acute toxicity (Inhalation) : Category 4
Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)

GHS label elements

Hazard pictograms :



Signal Word : Warning
Hazard Statements : H226 Flammable liquid and vapor.
H302 + H332 Harmful if swallowed or if inhaled.
H336 May cause drowsiness or dizziness.
Precautionary Statements : **Prevention:**

Eastman(TM) MAK

Version	Revision Date:	SDS Number:	Date of last issue: 06/21/2017
2.3	07/27/2018	150000001054	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Ingredients**

Chemical name	CAS-No.	Concentration (% w/w)
methyl amyl ketone	110-43-0	100

SECTION 4. FIRST AID MEASURES

If inhaled : Move to fresh air.
If breathed in, move person into fresh air.
If not breathing, give artificial respiration.
If symptoms persist, call a physician.

In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and water.

Eastman(TM) MAK

Version	Revision Date:	SDS Number:	Date of last issue: 06/21/2017
2.3	07/27/2018	150000001054	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Wash contaminated clothing before re-use.
If symptoms persist, call a physician.

In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
If eye irritation persists, consult a specialist.

If swallowed : Seek medical advice.

Most important symptoms and effects, both acute and delayed : Harmful if swallowed or if inhaled.
Harmful if swallowed or if inhaled.
May cause drowsiness or dizziness.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Use water spray to extinguish.
Dry chemical
Carbon dioxide (CO2)
Foam

Unsuitable extinguishing media : None known.

Hazardous combustion products : No hazardous combustion products are known

Further information : Flammable liquid and vapor.

Special protective equipment for fire-fighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Wear appropriate personal protective equipment.
Local authorities should be advised if significant spillages cannot be contained.

Environmental precautions : Avoid release to the environment.

Methods and materials for containment and cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not taste or swallow.
Avoid contact with skin.
Do not breathe vapors or spray mist.
Use only with adequate ventilation.

Eastman(TM) MAK

Version 2.3 PRD Revision Date: 07/27/2018 SDS Number: 150000001054 Date of last issue: 06/21/2017
 Date of first issue: 09/06/2016
 SDSUS / Z8 / 0001

Wash thoroughly after handling.

Conditions for safe storage : Keep container tightly closed and in a well-ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl amyl ketone	110-43-0	TWA	50 ppm	ACGIH
		TWA	100 ppm 465 mg/m ³	NIOSH REL
		TWA	100 ppm 465 mg/m ³	OSHA Z-1
		TWA	100 ppm 465 mg/m ³	OSHA P0

Engineering measures : Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Personal protective equipment

Respiratory protection : If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

Hand protection

Remarks : Wear suitable gloves.

Eye protection : Safety glasses with side-shields

Protective measures : Wear suitable protective equipment.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless

Eastman(TM) MAK

Version	Revision Date:	SDS Number:	Date of last issue: 06/21/2017
2.3	07/27/2018	150000001054	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Odor	:	pungent, sweet
Odor Threshold	:	0.2 ppm
pH	:	not determined
Melting point/range	:	-33 °F / -36 °C
Boiling point/boiling range	:	306 °F / 152 °C
Flash point	:	102 °F / 39 °C
		Method: closed cup
Evaporation rate	:	0.34
Self-ignition	:	739 °F / 393 °C
		Method: ASTM D2155
Vapor pressure	:	2.8 mbar (68 °F / 20 °C)
Relative vapor density	:	3.9
Relative density	:	0.81 (68 °F / 20 °C)
Solubility(ies)		
Water solubility	:	slightly soluble
Partition coefficient: n-octanol/water	:	Pow: 95.4 log Pow: 1.98
Autoignition temperature	:	not determined
Decomposition temperature	:	Method: DTA No exotherm to boiling
Viscosity		
Viscosity, dynamic	:	not determined
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Molecular weight	:	114.2 g/mol

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	None known. Stable

Eastman(TM) MAK

Version	Revision Date:	SDS Number:	Date of last issue: 06/21/2017
2.3	07/27/2018	150000001054	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	Carbon dioxide (CO2) Carbon monoxide

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

Acute oral toxicity	:	Remarks: No data available
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available

Ingredients:**methyl amyl ketone:**

Acute oral toxicity	:	LD50 Oral (Rat): 1,600 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 16.7 mg/l Exposure time: 4 h Test atmosphere: vapor
Acute dermal toxicity	:	LD50 Dermal (Rat): > 2,001 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : No data available

Ingredients:**methyl amyl ketone:**

Species	:	Rabbit
Exposure time	:	24 h
Result	:	No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : No data available

Eastman(TM) MAK

Version	Revision Date:	SDS Number:	Date of last issue: 06/21/2017
2.3	07/27/2018	150000001054	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Ingredients:**methyl amyl ketone:**

Species : Rabbit
 Result : slight irritation
 Exposure time : 24 h

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : No data available

Ingredients:**methyl amyl ketone:**

Test Type : Skin sensitization
 Species : Mouse
 Result : Does not cause skin sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Product:

Remarks : This information is not available.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Product:

Effects on fertility : Remarks: No data available

STOT-single exposure

May cause drowsiness or dizziness.

Product:

Eastman(TM) MAK

Version 2.3 PRD	Revision Date: 07/27/2018	SDS Number: 150000001054 SDSUS / Z8 / 0001	Date of last issue: 06/21/2017 Date of first issue: 09/06/2016
-----------------------	------------------------------	--	---

Remarks : No data available

STOT-repeated exposure

Not classified based on available information.

Product:

Remarks : No data available

Aspiration toxicity

Not classified based on available information.

Product:

No data available

Ingredients:**methyl amyl ketone:**

May be harmful if swallowed and enters airways.

Information on likely routes of exposure**Product:**

Inhalation : Remarks: Harmful if inhaled.

Skin contact : Remarks: None known.

Eye contact : Remarks: None known.

Ingestion : Remarks: Harmful if swallowed.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****methyl amyl ketone:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 131 mg/l
Exposure time: 96 h

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 98.2 mg/l
Test Type: Growth inhibition

Persistence and degradability**Ingredients:****methyl amyl ketone:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 69 %
Exposure time: 28 d

Eastman(TM) MAK

Version 2.3 PRD Revision Date: 07/27/2018 SDS Number: 150000001054 SDSUS / Z8 / 0001 Date of last issue: 06/21/2017 Date of first issue: 09/06/2016

Biochemical Oxygen Demand (BOD) : Biochemical oxygen demand within 5 days
1,770 mg/g

BOD-20:
2,000 mg/g

Chemical Oxygen Demand (COD) : 2,420 mg/g

Bioaccumulative potential**Ingredients:****methyl amyl ketone:**

Partition coefficient: n-octanol/water : Pow: 95.4
log Pow: 1.98

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 1110
Proper shipping name : n-Amyl methyl ketone
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1110
Proper shipping name : n-AMYL METHYL KETONE, n-Amyl methyl ketone

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-D

Eastman(TM) MAK

Version	Revision Date:	SDS Number:	Date of last issue: 06/21/2017
2.3	07/27/2018	150000001054	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1110
 Proper shipping name : n-Amyl methyl ketone

Class : CBL
 Packing group : III
 Labels : None
 ERG Code : 128
 Marine pollutant : no
 Remarks : combustible liquid, Packing group III for quantities of 450 liters (119 gallons) or more; not regulated for smaller quantities

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Acute toxicity (any route of exposure)
 Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Massachusetts Right To Know

methyl amyl ketone 110-43-0

Pennsylvania Right To Know

methyl amyl ketone 110-43-0

New Jersey Right To Know

Eastman(TM) MAK

Version 2.3 PRD Revision Date: 07/27/2018 SDS Number: 150000001054 SDSUS / Z8 / 0001 Date of last issue: 06/21/2017 Date of first issue: 09/06/2016

methyl amyl ketone

110-43-0

The ingredients of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- ISHL : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory
- TSCA : On the inventory, or in compliance with the inventory

TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH		2
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

Eastman(TM) MAK

Version	Revision Date:	SDS Number:	Date of last issue: 06/21/2017
2.3	07/27/2018	150000001054	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

1910.1000
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
 ACGIH / TWA : 8-hour, time-weighted average
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
 OSHA P0 / TWA : 8-hour time weighted average
 OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/27/2018

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8