

Eastman(TM) MPK

Version Revision Date: SDS Number: Date of last issue: 01/31/2022
2.5 05/20/2022 150000001116 Date of first issue: 09/06/2016
PRD

SECTION 1. IDENTIFICATION

Product name : Eastman(TM) MPK
Product code : 06548-00, P0654801, P0654806, P0654807, P0654808,
P0654809, P0654800, P0654810, E0654801

Manufacturer or supplier's details

Company name of supplier : Eastman Chemical Company
Address : 200 South Wilcox Drive
Kingsport TN 37660-5280
Telephone : (423) 229-2000
Emergency telephone : CHEMTREC: +1-800-424-9300, +1-703-527-3887 CCN7321

Recommended use of the chemical and restrictions on use

Recommended use : Solvent
Restrictions on use : None known.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids : Category 2
Acute toxicity (Oral) : Category 4
Eye irritation : Category 2A

GHS label elements

Hazard pictograms : 

Signal Word : Danger
Hazard Statements : H225 Highly flammable liquid and vapor.
H302 Harmful if swallowed.
H319 Causes serious eye irritation.
Precautionary Statements : **Prevention:**
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

Eastman(TM) MPK

Version	Revision Date:	SDS Number:	Date of last issue: 01/31/2022
2.5	05/20/2022	150000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Components

Chemical name	CAS-No.	Concentration (% w/w)
methyl propyl ketone	107-87-9	>= 90 - <= 100
methyl isobutyl ketone	108-10-1	>= 5 - < 10

Actual concentration is withheld as a trade secret

Eastman is committed to the safety, health and environment of our employees, our customers, and the communities we operate within. As part of this commitment, Eastman's Safety Data Sheets (SDS) are prepared in accordance with all applicable national and local regulations. The compositions of our documents reflect these requirements which include, but are not limited to, requirements under the Globally Harmonized System of Classification and Labeling (GHS). These compositions commonly involve the use of ranges versus specific analytical values. If you require a composition that is more specific, please refer to the Certificate of Analysis, sales specification, or contact your Customer Service Representative.

Eastman(TM) MPK

Version	Revision Date:	SDS Number:	Date of last issue: 01/31/2022
2.5	05/20/2022	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

SECTION 4. FIRST AID MEASURES

- If inhaled : Move to fresh air.
Treat symptomatically.
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and water.
Remove contaminated clothing and shoes.
Get medical attention if symptoms occur.
- In case of eye contact : Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.
- If swallowed : Seek medical advice.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed.
Causes serious eye irritation.
Harmful if swallowed.
Causes serious eye irritation.
- Notes to physician : Treat symptomatically.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO2)
Dry chemical
Water spray
- Unsuitable extinguishing media : Water spray jet
- Specific hazards during fire fighting : Water may be ineffective.
The product will float on water and can be reignited on surface water.
- Hazardous combustion products : No hazardous combustion products are known
- Further information : Use water spray to cool unopened containers.
- Special protective equipment for fire-fighters : Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Wear appropriate personal protective equipment.
Local authorities should be advised if significant spillages cannot be contained.
-

Eastman(TM)MPK

Version	Revision Date:	SDS Number:	Date of last issue: 01/31/2022
2.5	05/20/2022	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Environmental precautions : Avoid release to the environment.

Methods and materials for containment and cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
After cleaning, flush away traces with water.
Eliminate all ignition sources if safe to do so.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : None known.

Advice on safe handling : Avoid inhalation of vapor or mist.
Do not get in eyes.
Avoid contact with skin, eyes and clothing.
Do not swallow.
Ensure adequate ventilation.
Wash thoroughly after handling.
Keep away from fire (No Smoking).
Keep away from fire, sparks and heated surfaces.
Do not use sparking tools.

Conditions for safe storage : Keep container closed when not in use.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl propyl ketone	107-87-9	STEL	150 ppm	ACGIH
		TWA	150 ppm 530 mg/m ³	NIOSH REL
		TWA	200 ppm 700 mg/m ³	OSHA Z-1
		TWA	200 ppm 700 mg/m ³	OSHA P0
		STEL	250 ppm 875 mg/m ³	OSHA P0
methyl isobutyl ketone	108-10-1	TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
		ST	75 ppm 300 mg/m ³	NIOSH REL
		TWA	50 ppm 205 mg/m ³	NIOSH REL
		TWA	100 ppm 410 mg/m ³	OSHA Z-1
		TWA	50 ppm 205 mg/m ³	OSHA P0

Eastman(TM) MPK

Version Revision Date: SDS Number: Date of last issue: 01/31/2022
 2.5 05/20/2022 150000001116 Date of first issue: 09/06/2016
 PRD SDSUS / Z8 / 0001

		STEL	75 ppm 300 mg/m3	OSHA P0
--	--	------	---------------------	---------

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Remarks : Wear suitable gloves.

Eye protection : Wear safety glasses with side shields (or goggles).
 Face-shield
 Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.

Protective measures : Remove respiratory and skin/eye protection only after vapors have been cleared from the area.
 Ensure that eye flushing systems and safety showers are located close to the working place.
 Use personal protective equipment as required.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : colorless

Odor : alcohol-like

Odor Threshold : 11 ppm

pH : not determined

Melting point/range : -108 °F / -78 °C

Boiling point/boiling range : 214 °F / 101 °C

Flash point : 46.0 °F / 7.8 °C
 Method: Tag closed cup

Evaporation rate : 2.3

Eastman(TM) MPK

Version	Revision Date:	SDS Number:	Date of last issue: 01/31/2022
2.5	05/20/2022	150000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Self-ignition	:	842 °F / 450 °C 1,013 hPa
Upper explosion limit / Upper flammability limit	:	8.7 %(V)
Lower explosion limit / Lower flammability limit	:	1.56 %(V)
Vapor pressure	:	37 mbar (68 °F / 20 °C)
Relative vapor density	:	2.9
Relative density	:	0.81 (68 °F / 20 °C)
Solubility(ies) Water solubility	:	Moderate
Partition coefficient: n-octanol/water	:	log Pow: 0.857 (68 °F / 20 °C)
Autoignition temperature	:	840 °F / 449 °C Method: ASTM D2155
Decomposition temperature	:	Method: DTA No exotherm to boiling
Viscosity Viscosity, dynamic	:	0.607 mPa.s (68 °F / 20 °C)
Viscosity, kinematic	:	not determined
Explosive properties	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous decomposition products formed under fire conditions.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	Carbon dioxide (CO2) Carbon monoxide

Eastman(TM) MPK

Version	Revision Date:	SDS Number:	Date of last issue: 01/31/2022
2.5	05/20/2022	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Harmful if swallowed.

Product:

Acute oral toxicity : Remarks: Harmful if swallowed.

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Components:**methyl isobutyl ketone:**

Acute oral toxicity : LD50 Oral (Rat): 2,080 mg/kg

Acute inhalation toxicity : LC50 (Rat): 16.4 mg/l
Exposure time: 4 h
Test atmosphere: vapor**Skin corrosion/irritation**

Not classified based on available information.

Product:

Assessment : Causes mild skin irritation.

Components:**methyl propyl ketone:**Species : Guinea pig
Exposure time : 24 h
Result : slight**methyl isobutyl ketone:**Species : Rabbit
Exposure time : 72 h
Result : none**Serious eye damage/eye irritation**

Causes serious eye irritation.

Product:

Assessment : Causes serious eye irritation.

Components:**methyl isobutyl ketone:**Species : Rabbit
Result : Eye irritation

Eastman(TM) MPK

Version Revision Date: SDS Number: Date of last issue: 01/31/2022
2.5 05/20/2022 15000001116 Date of first issue: 09/06/2016
PRD SDSUS / Z8 / 0001

STOT-single exposure

Not classified based on available information.

Product:

Remarks : No data available

STOT-repeated exposure

Not classified based on available information.

Product:

Remarks : No data available

Repeated dose toxicity**Product:**

Remarks : No data available

Aspiration toxicity

Not classified based on available information.

Product:

May be harmful if swallowed and enters airways.

Components:**methyl isobutyl ketone:**

May be harmful if swallowed and enters airways.

Experience with human exposure**Product:**

Inhalation : Remarks: None known.

Skin contact : Remarks: None known.

Eye contact : Remarks: Causes serious eye irritation.

Ingestion : Remarks: Harmful if swallowed.

Further information**Product:**

Remarks : None known.

Eastman(TM) MPK

Version	Revision Date:	SDS Number:	Date of last issue: 01/31/2022
2.5	05/20/2022	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****methyl propyl ketone:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,240 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 110 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : NOEC: (Chlorella pyrenoidosa): 74 mg/l
plants Exposure time: 72 h

EC50 (Chlorella pyrenoidosa): 150 mg/l
Exposure time: 72 h

methyl isobutyl ketone:

Toxicity to fish : LC50 (goldfish): 460 mg/l
Exposure time: 24 h

LC50 (golden orfe): 675 - 750 mg/l
Exposure time: 48 h

Toxicity to daphnia and other : LC50 (Daphnia magna (Water flea)): 4,300 mg/l
aquatic invertebrates Exposure time: 24 h

LC50 (Crangon crangon (shrimp)): 1,250 mg/l
Exposure time: 24 h

Persistence and degradability**Components:****methyl propyl ketone:**

Biodegradability : Result: Readily biodegradable

Biochemical Oxygen De- : BOD-5:
mand (BOD) 1,380 mg/g

BOD-20:
1,800 mg/g

Chemical Oxygen Demand : 1,800 mg/g
(COD)

methyl isobutyl ketone:

Biodegradability : Result: Readily biodegradable

Biochemical Oxygen De- : BOD-5:

Eastman(TM) MPK

Version	Revision Date:	SDS Number:	Date of last issue: 01/31/2022
2.5	05/20/2022	15000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

mand (BOD)	1,940 - 2,060 mg/g
Chemical Oxygen Demand (COD)	: 2,160 - 2,460 mg/g
ThOD	: 2,720 mg/g

Bioaccumulative potential**Components:****methyl propyl ketone:**

Partition coefficient: n-octanol/water : Pow: 0.857 (68 °F / 20 °C)

methyl isobutyl ketone:

Partition coefficient: n-octanol/water : Pow: 24
log Pow: 1.38

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No.	: UN 1224
Proper shipping name	: Ketones, liquid, n.o.s. (methyl propyl ketone, methyl isobutyl ketone)
Class	: 3
Packing group	: II
Labels	: Flammable Liquids
Packing instruction (cargo aircraft)	: 364
Packing instruction (passenger aircraft)	: 353

IMDG-Code

UN number	: UN 1224
Proper shipping name	: KETONES, LIQUID, N.O.S. (methyl propyl ketone, methyl isobutyl ketone)
Class	: 3

Eastman(TM) MPK

Version	Revision Date:	SDS Number:	Date of last issue: 01/31/2022
2.5	05/20/2022	150000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

Packing group : II
 Labels : 3
 EmS Code : F-E, S-D
 Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

UN/ID/NA number : UN 1224
 Proper shipping name : Ketones, liquid, n.o.s.
 (methyl propyl ketone, methyl isobutyl ketone)
 Class : 3
 Packing group : II
 Labels : FLAMMABLE LIQUID
 ERG Code : 127
 Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
methyl isobutyl ketone	108-10-1	5000	

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Acute toxicity (any route of exposure)
 Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

methyl isobutyl 108-10-1
 ketone

California Prop. 65

WARNING: This product can expose you to chemicals including methyl isobutyl ketone, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

Eastman(TM)MPK

Version	Revision Date:	SDS Number:	Date of last issue: 01/31/2022
2.5	05/20/2022	150000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

TCSI	:	On the inventory, or in compliance with the inventory
TSCA	:	All substances listed as active on the TSCA inventory
AIC	:	On the inventory, or in compliance with the inventory
DSL	:	All components of this product are on the Canadian DSL
ENCS	:	On the inventory, or in compliance with the inventory
ISHL	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
NZloC	:	On the inventory, or in compliance with the inventory
TECI	:	On the inventory, or in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.


No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION**Further information**

Eastman(TM) MPK

Version
2.5
PRDRevision Date:
05/20/2022SDS Number:
150000001116
SDSUS / Z8 / 0001Date of last issue: 01/31/2022
Date of first issue: 09/06/2016

NFPA 704:



HMIS® IV:

HEALTH	/	2
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average

AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to

Eastman(TM) MPK

Version	Revision Date:	SDS Number:	Date of last issue: 01/31/2022
2.5	05/20/2022	150000001116	Date of first issue: 09/06/2016
PRD		SDSUS / Z8 / 0001	

50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/20/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8