

SAFETY DATA SHEET

FOR INDUSTRIAL USE ONLY

EPON[™] Resin 828

Section 1. Product and company identification

GHS product identifier : EPON[™] Resin 828

MSDS Number : K122F
Product type : Epoxy Resin

Material uses : Epoxy Resin Systems

Manufacturer/Supplier/Impor Alliance Chemical **ter** 204 South Edmond St

Taylor, Texas, 76574 512-365-6838

Contact person sales@alliancechemical.com

Telephone 5123656838

Emergency telephone number : For Emergency Medical Assistance

CHEMTEL (800) 255-3924 (24 Hours/

Day, 7 Days/Week)

Section 2. Hazards identification

Classification of the substance or

mixture

: SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A SKIN SENSITISATION - Category 1

GHS label elements

Hazard pictograms :

(!)

Signal word : Warning

Hazard statements : H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

Precautionary statements

 $EPON^{\text{TM}}$ Resin 828 Page: 2/13

General : Not applicable.

Prevention: Wear eye or face protection.

Avoid breathing vapor.

Wash thoroughly after handling.

Response : Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

IF ON SKIN:

Wash with plenty of water.

IF IN EYES:

Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

If eye irritation persists:

Get medical advice or attention.

Storage : Not applicable.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

Other hazards which do not result

in classification

None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% by weight	CAS
		number
4,4'-Isopropylidenediphenol-Epichlorohydrin Copolymer	100	25068-38-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact: Wash with plenty of soap and water. Remove contaminated clothing

 $EPON^{\text{TM}}$ Resin 828 Page: 3/13

and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first aid personnel : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Unsuitable extinguishing media Use an extinguishing agent suitable for the surrounding fire.

: None known.

Specific hazards arising from the chemical

Hazardous thermal decomposition products

In a fire or if heated, a pressure increase will occur and the container may burst.

 Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

 $EPON^{\text{IM}}$ Resin 828 Page: 4/13

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13 of SDS). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Keep container tightly closed and sealed until ready for use.

EPON™ Resin 828

Exposure limits

Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Ingredient name

Eye/face protection

Occupational exposure limits

Ingredient name	Exposure limits
4,4'-Isopropylidenediphenol- Epichlorohydrin Copolymer	None.
Recommended monitoring procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required. If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering controls	
Environmental exposure controls :	
<u>Individual protection measures</u>	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash

Version: 20.0 Date of issue/Date of revision: 07/28/2020 Date of previous issue: 09/25/2018

contaminated clothing before reusing. Ensure that eyewash stations

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to

following protection should be worn, unless the assessment indicates a

liquid splashes, mists, gases or dusts. If contact is possible, the

and safety showers are close to the workstation location.

higher degree of protection: chemical splash goggles.

 $EPON^{\text{TM}}$ Resin 828 Page: 6/13

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves

cannot be accurately estimated.

Body protection: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

Respiratory protection: Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Viscous liquid.

Color : Clear.

Odor : Not available
Odor threshold : Not available

pH : Not available

Melting point/ Freezing point : Not available **Boiling point** : 260 °C (500 °F)

Flash point : Pensky-Martens Closed Cup: 251 °C (484 °F) (ASTM D 93)

Burning time: Not availableBurning rate: Not availableEvaporation rate: Not available

Flammability (solid, gas) : Not available

Lower and upper explosive : Lower: Not available (flammable) limits : Upper: Not available

Vapor pressure : 0.03 mbar @ 77 °C (171 °F)

Vapor density : Not available

Relative density : 1.17

Solubility : Not available

 $EPON^{\text{TM}}$ Resin 828 Page: 7/13

Solubility in water : Negligible

Partition coefficient: n- : Not available

octanol/water

Auto-ignition temperature : Not available

Decomposition temperature : Not available **SADT** : Not available

Viscosity : Dynamic: Not available

Kinematic: Not available

Other information

No additional information.

Section 10. Stability and reactivity

Reactivity : Stable under normal conditions.

Chemical stability : The product is stable.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will

not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

Other hazards Reacts with considerable heat release with some curing agents.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
4,4'-Isopropylidenediphenol-F	Epichlorohydrin Cop	olymer		
	LD50 Oral	Rat	11,400 mg/kg	-
	LD50 Dermal	Rat	2,000 mg/kg	=

Conclusion/Summary : Not available

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
4,4'-Isopropylidenediphenol-	Skin -	Rabbit	1.5 - 2		-
Epichlorohydrin Copolymer	Erythema/E				
	schar 404				
	Acute				
	Dermal				

EPON™ Resin 828

Irritation/Co				
rrosion				
Skin -	Rabbit	1.0 - 1.5		-
Edema 404				
Acute				
Dermal				
Irritation/Co				
rrosion				
eyes 405	Rabbit	0		-
Acute Eye				
Irritation/Co				
rrosion				
eyes -	Rabbit	0.7		-
Redness of				
the				
conjunctiva				
e				
Skin -	Rabbit		24 hrs	-
Moderate				
irritant				
Skin -	Rabbit		24 hrs	-
Severe				
irritant				
eyes - Mild	Rabbit			-
irritant				

Conclusion/Summary

Skin:Not availableeyes:Not availableRespiratory:Not available

Sensitization

Conclusion/Summary

Skin: Not availableRespiratory: Not available

Mutagenicity

Product/ingredient name	Test	Experiment	Result	
4,4'-Isopropylidenediphenol-	-	; Mammalian-	Negative	
Epichlorohydrin Copolymer		Animal		
Remarks:	Did not induce evidence of chromosome damage in a mouse dominant lethal oral			
	gavage study conducted up to a high dose level of 10 grams/kg and in a mouse			
	micronucleus test conducted up to a high dose of 5000 mg/kg. Negative in a male			
	mouse spermatocyte cytogenetic assay with treatment for 5 days by oral gavage up			
	to a high dose of 3000 mg/kg. Did not induce an increase in the frequency of			
	chromosome damage in a Chinese hamster bone marrow cytogenetic test by oral			
	gavage up to a high dose of 3300 mg/kg. Failed to induce an increase of DNA			
	strand breaks in rat liver cells following oral gavage treatment with 500 mg/kg as			
	measured by alkaline elution.			

Conclusion/Summary : Not available

Carcinogenicity

Conclusion/Summary : Not available

EPON™ *Resin 828 Page:9/13*

Reproductive toxicity

Conclusion/Summary : Not available

Teratogenicity

Conclusion/Summary : Not available

Specific target organ toxicity (single exposure)

Not available

Specific target organ toxicity (repeated exposure)

Not available

Aspiration hazard

Not available

Information on likely routes of

Not available

exposure

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes skin irritation. May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No specific data.

Skin contact : Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate effects : Not available **Potential delayed effects** : Not available

Long term exposure

Potential immediate effects : Not available
Potential delayed effects : Not available

Potential chronic health effects

Conclusion/Summary : Not available

EPON™ Resin 828Page: 10/13

General : Once sensitized, a severe allergic reaction may occur when

subsequently exposed to very low levels.

Carcinogenicity: No known significant effects or critical hazards.Mutagenicity: No known significant effects or critical hazards.Teratogenicity: No known significant effects or critical hazards.Developmental effects: No known significant effects or critical hazards.Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral	Dermal	Inhalation (gases)	Inhalation (vapors)	Inhalation (dusts and mists)
EPON TM Resin 828	11,400 mg/kg	N/A	N/A	N/A	N/A
Phenol, 4,4'-(1- methylethylidene)bis-, polymer with 2- (chloromethyl)oxirane	11,400 mg/kg	N/A	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
bis-[4-(2,3-epoxipropoxi)pheny]	[]propane		
	Acute LC50 1.3 mg/l - 203 Fish, Acute	Fish - Fish	96 h
	Toxicity Test		
	Acute EC50 2.1 mg/l - 202 Daphnia	Aquatic invertebrates.	48 h
	sp. Acute Immobilization Test and	Water flea	
	Reproduction Test		
	Acute $LC50 > 11 \text{ mg/l}$ -	Aquatic plants - Algae	72 h
	Chronic No-observable-effect-	Aquatic invertebrates.	21 d
	concentration 0.3 mg/l semi-static test	Water flea	
	211 Daphnia Magna Reproduction Test		

Conclusion/Summary : Not available

Persistence/degradability

Conclusion/Summary : Not available

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
bis-[4-(2,3-	2.64 - 3.78	3 - 31 31.00	low
epoxipropoxi)phenyllpropane			

Mobility in soil

 $EPON^{\text{IM}}$ Resin 828 Page: 11/13

Soil/water partition coefficient

(KOC)

Other adverse effects : No known significant effects or critical hazards.

Not available

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

The data provided in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulations to properly classify your shipment for transportation.

Regulatory information	UN/NA number	Proper shipping name	Classes/*PG	Reportable Quantity (RQ)
CFR		Non-regulated		
TDG		Non-regulated		
IMO/IMDG	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (LIQUID EPOXY RESIN)	Class 9 III	
IATA (Cargo)	3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (LIQUID EPOXY RESIN)	Class 9 III	

*PG: Packing group

Environmentally hazardous and/or Marine Pollutant : Yes.



 $EPON^{\text{TM}}$ Resin 828 Page: 12/13

Special precautions for user

: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

United States

U.S. Federal regulations

: United States - TSCA 12(b) - Chemical export notification: None required.

United States - TSCA $5\alpha 2$ - Final significant new use rules: Not listed United States - TSCA $5\alpha 2$ - Proposed significant new use rules: Not listed

United States - TSCA 5(e) - Substances consent order: Not listed SARA 311/312 Classification - SKIN IRRITATION, Category 2 SARA 311/312 Classification - EYE IRRITATION, Category 2A

SARA 311/312 Classification - SKIN SENSITISATION, Category 1

SARA 311/312 Classification - Not applicable

California Prop. 65:

WARNING: This product may contain one or more chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

United States inventory (TSCA: All components are active or exempted. **8b**)

International regulations

International lists

: Australia inventory (AICS): All components are listed or exempted.

Canada inventory: All components are listed or exempted. **Japan inventory:** All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted. **Korea inventory (KECI):** All components are listed or exempted.

New Zealand Inventory (NZIoC): All components are listed or exempted. Philippines inventory (PICCS): All components are listed or exempted. United States inventory (TSCA 8b): All components are active or exempted.

Taiwan inventory (TCSI): All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System III (U.S.A.):

Health	*	2
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS®

 $EPON^{\text{TM}}$ Resin 828 Page: 13/13

materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Full text of abbreviated H : Not applicable.

History

statements

Date of printing: 03/23/2021Date of issue/Date of revision: 07/28/2020Date of previous issue: 09/25/2018Version: 20.0

Prepared by

Key to abbreviations

: Product Safety Stewardship

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

RID = The Regulations concerning the International Carriage of Dangerous Goods by

Rail

UN = United Nations

References : Not available

Notice to reader

The information provided herein was believed by Alliance Chemical to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Alliance Chemical are subject to Alliance Chemical's terms and conditions of sale. Alliance Chemical MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY Alliance Chemical, except that the product shall conform to Alliance Chemical's specifications.