

MPK

SECTION 1. IDENTIFICATION

Product name MPK

Product code

Manufacturer or supplier's details				
Company name of supplier	Alliance Chemical 204 South Edmond St			
Address	Taylor, Texas, 76574 512-365-6838			
Telephone				
Emergency telephone	: CHEMTEL (800) 255-3924 (24 Hours/Day, 7 Days/Week)			
Recommended use of the o	hemical and restrictions on use			
Recommended use	: Solvent			
Restrictions on use	: None known.			

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accord 1910.1200)	lan	ce with the OSHA Hazard Communication Standard (29 CFR
Flammable liquids	:	Category 2
Acute toxicity (Oral)	:	Category 4
Eye irritation	:	Category 2A
GHS label elements Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H225 Highly flammable liquid and vapor. H302 Harmful if swallowed. H319 Causes serious eye irritation.
Precautionary Statements	:	Prevention: P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

ersion .5 RD	Revision Date: 05/20/2022	SDS Number: 150000001116 SDSUS / Z8/ 0001	Date of last issue: 01/31/2022 Date of first issue: 09/06/2016
		P240 Ground/bo P241 Use explo ment. P242 Use only P243 Take pred P264 Wash ski P270 Do not ea	tainer tightly closed. ond container and receiving equipment. osion-proof electrical/ventilating/lighting/equip- non-sparking tools. cautionary measures against static discharge. n thoroughly after handling. at, drink or smoke when using this product. tective gloves/ eye protection/ face protection.
		CENTER/ doctor P303 + P361 + all contaminated P305 + P351 + for several minu to do. Continue P337 + P313 lf tion. P370 + P378 lm	P330 IF SWALLOWED: Call a POISON or if you feel unwell. Rinse mouth. P353 IF ON SKIN (or hair): Take off immediately d clothing. Rinse skin with water/ shower. P338 IF IN EYES: Rinse cautiously with water utes. Remove contact lenses, if present and easy rinsing. eye irritation persists: Get medical advice/ atten- a case of fire: Use dry sand, dry chemical or alco- am to extinguish.
		Storage: P403 + P235 S	tore in a well-ventilated place. Keep cool.
		Disposal: P501 Dispose o posal plant.	of contents/ container to an approved waste dis-
	r hazards known.		

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Components

Chemical name	CAS-No.	Concentration (% w/w)
methyl propyl ketone	107-87-9	>= 90 - <= 100
methyl isobutyl ketone	108-10-1	>= 5 - < 10

Actual concentration is withheld as a trade secret

Eastman is committed to the safety, health and environment of our employees, our customers, and the communities we operate within. As part of this commitment, Eastman's Safety Data Sheets (SDS) are prepared in accordance with all applicable national and local regulations. The compositions of our documents reflect these requirements which include, but are not limited to, requirements under the Globally Harmonized System of Classification and Labeling (GHS). These compositions commonly involve the use of ranges versus specific analytical values. If you require a composition that is more specific , please refer to the Certificate of Analysis, sales specification, or contact your Customer Service Representative.

Version	Revision Date:	SDS Number:	Date of last issue: 01/31/2022
2.5 PRD	05/20/2022	150000001116 SDSUS / Z8/ 0001	Date of first issue: 09/06/2016

SECTION 4. FIRST AID MEASURES

If inhaled	:	Move to fresh air. Treat symptomatically. If symptoms persist, call a physician.
In case of skin contact	:	Wash off with soap and water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
In case of eye contact	:	Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.
If swallowed	:	Seek medical advice.
Most important symptoms and effects, both acute and delayed	:	Harmful if swallowed. Causes serious eye irritation. Harmful if swallowed. Causes serious eye irritation.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Carbon dioxide (CO2) Dry chemical Water spray
Unsuitable extinguishing media	:	Water spray jet
Specific hazards during fire fighting	:	Water may be ineffective. The product will float on water and can be reignited on surface water.
Hazardous combustion prod- ucts	:	No hazardous combustion products are known
Further information	:	Use water spray to cool unopened containers.
Special protective equipment for fire-fighters	:	Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec-	:	Wear appropriate personal protective equipment.
tive equipment and emer-		Local authorities should be advised if significant spillages
gency procedures		cannot be contained.

MPK

Vers 2.5 PRD	sion	Revision Date: 05/20/2022	15	DS Number: 0000001116 SUS / Z8/ 0001	Date of last issue: 01/31/2022 Date of first issue: 09/06/2016
	Method	mental precautions Is and materials for ment and cleaning up	:	material, (e.g. sar and transfer to a national regulation After cleaning, flue	he environment. soak up with non-combustible absorbent nd, earth, diatomaceous earth, vermiculite) container for disposal according to local / ns (see section 13). sh away traces with water. on sources if safe to do so.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	None known.
Advice on safe handling	:	Avoid inhalation of vapor or mist. Do not get in eyes. Avoid contact with skin, eyes and clothing. Do not swallow. Ensure adequate ventilation. Wash thoroughly after handling. Keep away from fire (No Smoking). Keep away from fire, sparks and heated surfaces. Do not use sparking tools.
Conditions for safe storage	:	Keep container closed when not in use.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
methyl propyl ketone	107-87-9	STEL	150 ppm	ACGIH
		TWA	150 ppm 530 mg/m3	NIOSH REL
		TWA	200 ppm 700 mg/m3	OSHA Z-1
		TWA	200 ppm 700 mg/m3	OSHA P0
		STEL	250 ppm 875 mg/m3	OSHA P0
methyl isobutyl ketone	108-10-1	TWA	20 ppm	ACGIH
		STEL	75 ppm	ACGIH
		ST	75 ppm 300 mg/m3	NIOSH REL
		TWA	50 ppm 205 mg/m3	NIOSH REL
		TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	50 ppm 205 mg/m3	OSHA P0

Ver 2.5 PRD	sion	Revision Date: 05/20/2022	15	DS Number: 60000001116 0SUS / Z8/ 0001		t issue: 01/31/2022 t issue: 09/06/2016		
					STEL	75 ppm 300 mg/m3	OSHA P0	
	Engin	eering measures	:	Ensure adequ	ate ventilation.			
	Perso	nal protective equip	nen	t				
	Respiratory protection Hand protection Remarks		:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.				
			:	Wear suitable gloves.				
	Eye protection		:	Wear safety glasses with side shields (or goggles). Face-shield Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.				
	Protec	tive measures	:	have been cle Ensure that en located close	eared from the a ye flushing system to the working p	ems and safety show	·	
	Hygier	e measures	:	Handle in acc practice.	ordance with go	od industrial hygiene	e and safety	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: colorless
Odor	: alcohol-like
Odor Threshold	: 11 ppm
рН	: not determined
Melting point/range	: -108 °F / -78 °C
Boiling point/boiling range	: 214 °F / 101 °C
Flash point	: 46.0 °F / 7.8 °C
	Method: Tag closed cup
Evaporation rate	: 2.3

Vers 2.5 PRD	sion	Revision Date: 05/20/2022	150	S Number: 0000001116 5US / Z8/ 0001	Date of last issue: 01/31/2022 Date of first issue: 09/06/2016
	Self-ign	ition	:	842 °F / 450 °C 1,013 hPa	
		explosion limit / Upper bility limit	:	8.7 %(V)	
		explosion limit / Lower bility limit	:	1.56 %(V)	
	Vapor p	pressure	:	37 mbar (68 °F /	20 °C)
	Relative	e vapor density	:	2.9	
	Relative	e density	:	0.81 (68 °F / 20 °	°C)
	Solubili Wat	ty(ies) er solubility	:	Moderate	
	Partition octanol	n coefficient: n- /water	:	log Pow: 0.857 (6	68 °F / 20 °C)
	Autoign	ition temperature	:	840 °F / 449 °C Method: ASTM D	02155
	Decom	position temperature	:	Method: DTA No exotherm to b	ooiling
	Viscosi Visc	ty cosity, dynamic	:	0.607 mPa.s (68	°F / 20 °C)
		cosity, kinematic	:		
	Explosi	ve properties	:	No data available	
	Oxidizir	ng properties	:	No data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reac- tions	:	Hazardous decomposition products formed under fire conditions.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	Carbon dioxide (CO2) Carbon monoxide

MPK

Version 2.5 PRD	Revision Date: 05/20/2022	SDS Number: 150000001116 SDSUS / Z8/ 0001	Date of last issue: 01/31/2022 Date of first issue: 09/06/2016
SECTION	11. TOXICOLOGICA	L INFORMATION	

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity	:	Remarks: Harmful if swallowed.
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Remarks: No data available

Components:

methyl isobutyl ketone: Acute oral toxicity	:	LD50 Oral (Rat): 2,080 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 16.4 mg/l Exposure time: 4 h Test atmosphere: vapor

Skin corrosion/irritation

Not classified based on available information.

Product:

: Causes mild skin irritation.

Components:

Assessment

methyl propyl ketone:

Species	:	Guinea pig
Exposure time	:	24 h
Result	:	slight

methyl isobutyl ketone:

Species	:	Rabbit
Exposure time	:	72 h
Result	:	none

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Assessment :	Causes serious	eye irritation.
--------------	----------------	-----------------

Components:

methyl isobutyl ketone:

Species	:	Rabbit
Result	:	Eye irritation

MPK

rsion)	Revision Date: 05/20/2022	SDS Number: 150000001116 SDSUS / Z8/ 0001	Date of last issue: 01/31/2022 Date of first issue: 09/06/2016
Respira	atory or skin sensi	tization	
Skin se	nsitization		
Not clas	ssified based on ava	ailable information.	
-	atory sensitization ssified based on ava	ailable information.	
<u>Produc</u>	<u>t:</u>		
Remark	S	: No data available	9
	ell mutagenicity ssified based on ava	ailable information.	
<u>Compo</u>	nents:		
-	propyl ketone:		
Genoto	xicity in vitro	Metabolic activa	ionella typhimurium assay (Ames test) tion: +/-activation al Reverse Mutation Assay
		Metabolic activa	genicity - Mammalian tion: +/- activation Mammalian Cell Gene Mutation Test
		Metabolic activa	genicity - Mammalian tion: +/- activation Mammalian Chromosome Aberration Test
	ogenicity ssified based on ava	ailable information.	
Produc			
Remark		: This information	is not available.
IARC		Possibly carcinogenic to butyl ketone) humans 108-10-1
OSHA		nent of this product pres list of regulated carcino	ent at levels greater than or equal to 0.1% is gens.
NTP		ent of this product prese s a known or anticipated	nt at levels greater than or equal to 0.1% is a carcinogen by NTP.
-	luctive toxicity ssified based on ava	ailable information.	
Produc Effects	<u>t:</u> on fertility	: Remarks: No da	ta available

ersion 5 D	Revision Date: 05/20/2022	SDS Num 15000000 SDSUS / Z8	1116	Date of last issue: 01/31/2022 Date of first issue: 09/06/2016
	-single exposure lassified based on ava	ilable informa	ition.	
<u>Produ</u>	uct:			
Rema	urks	: No da	ta available	
	-repeated exposure lassified based on ava	ilable informa	ition.	
<u>Produ</u>				
Rema	ırks	: No da	ta available	
Repe	ated dose toxicity			
<u>Prod</u>	uct:			
Rema	urks	: No da	ta available	
-	ation toxicity lassified based on ava	ilable informa	ition.	
Produ	uct:			
May t	be harmful if swallowe	d and enters	airways.	
<u>Com</u>	<u>oonents:</u>			
	yl isobutyl ketone: be harmful if swallowe	d and enters	airways.	
Ехре	rience with human e	xposure		
<u>Produ</u>	uct:			
Inhala	tion	: Rema	rks: None k	nown.
Skin o	contact	: Rema	rks: None k	nown.
Eye c	ontact	: Rema	rks: Causes	s serious eye irritation.
Ingest	tion	: Rema	rks: Harmfu	I if swallowed.
Furth	er information			
<u>Produ</u>	uct:			
Rema	ırks	: None	known.	

 Version
 Revision Date:
 SDS Number:

 2.5
 05/20/2022
 15000001116

 PRD
 SDSUS / Z8 / 0001

Date of last issue: 01/31/2022 Date of first issue: 09/06/2016

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

methyl propyl ketone:		
Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 1,240 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 110 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	NOEC: (Chlorella pyrenoidosa): 74 mg/l Exposure time: 72 h
		EC50 (Chlorella pyrenoidosa): 150 mg/l Exposure time: 72 h
methyl isobutyl ketone:		
Toxicity to fish	:	LC50 (goldfish): 460 mg/l Exposure time: 24 h
		LC50 (golden orfe): 675 - 750 mg/l Exposure time: 48 h
Toxicity to daphnia and other aquatic invertebrates	:	LC50 (Daphnia magna (Water flea)): 4,300 mg/l Exposure time: 24 h
		LC50 (Crangon crangon (shrimp)): 1,250 mg/l Exposure time: 24 h

Persistence and degradability

Components:

methyl propyl ketone: Biodegradability	:	Result: Readily biodegradable
Biochemical Oxygen De- mand (BOD)	:	BOD-5: 1,380 mg/g
		BOD-20: 1,800 mg/g
Chemical Oxygen Demand (COD)	:	1,800 mg/g
methyl isobutyl ketone:		
Biodegradability	:	Result: Readily biodegradable
Biochemical Oxygen De-	:	BOD-5:

MPK

Vers 2.5 PRD	sion	Revision Date: 05/20/2022	15	DS Number: 0000001116 SUS / Z8/ 0001	Date of last issue: 01/31/2022 Date of first issue: 09/06/2016
	mand (BOD)		1,940 - 2,060 mg/	'g
	Chemical Oxygen Demand (COD)		:	2,160 - 2,460 mg/	'g
	ThOD		:	2,720 mg/g	
	Bioacc	umulative potential			
	Compo	onents:			
	methyl	propyl ketone:			
	-	n coefficient: n-	:	Pow: 0.857 (68 °F	= / 20 °C)
	methyl	isobutyl ketone:			
	Partition octanol	n coefficient: n- /water	:	Pow: 24 log Pow: 1.38	
	Mobilit	y in soil			
	No data	a available			
	Other a	adverse effects			
	No data available				

Disposal methods		
Waste from residues	:	Dispose of in accordance with local regulations.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR		
UN/ID No.	:	UN 1224
Proper shipping name	:	Ketones, liquid, n.o.s. (methyl propyl ketone, methyl isobutyl ketone)
Class	:	3
Packing group	:	II
Labels	:	Flammable Liquids
Packing instruction (cargo aircraft)	:	364
Packing instruction (passen- ger aircraft)	:	353
IMDG-Code		
UN number	:	UN 1224
Proper shipping name	:	KETONES, LIQUID, N.O.S. (methyl propyl ketone, methyl isobutyl ketone)
Class	:	3

Version 2.5 PRD	Revision Date: 05/20/2022	15	DS Number: 0000001116 0SUS / Z8/ 0001	Date of last issue: 01/31/2022 Date of first issue: 09/06/2016
Labels EmS	-	:	ll 3 F-E, S-D no	
Transport in bulk according Not applicable for product as				OL 73/78 and the IBC Code
Dome	estic regulation			
Prope	/NA number r shipping name	:	UN 1224 Ketones, liquid, n (methyl propyl ke 3 II	.o.s. etone, methyl isobutyl ketone)
Labels ERG	-	:	II FLAMMABLE LIG 127 no	lud

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
methyl isobutyl ketone	108-10-1	5000	

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	:	Flammable (gases, aerosols, liquids, or solids) Acute toxicity (any route of exposure) Serious eye damage or eye irritation
SARA 313	:	The following components are subject to reporting levels established by SARA Title III, Section 313:
		methyl isobutyl 108-10-1 ketone

California Prop. 65

WARNING: This product can expose you to chemicals including methyl isobutyl ketone, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

MPK

Version 2.5 PRD	Revision Date: 05/20/2022	15	DS Number: 0000001116 SUS / Z8/ 0001	Date of last issue: 01/31/2022 Date of first issue: 09/06/2016
TCSI		:	On the inventory,	or in compliance with the inventory
TSCA		:	All substances lis	ted as active on the TSCA inventory
AIIC		:	On the inventory,	or in compliance with the inventory
DSL		:	All components of	f this product are on the Canadian DSL
ENCS		:	On the inventory,	or in compliance with the inventory
ISHL		:	On the inventory,	or in compliance with the inventory
KECI		:	On the inventory,	or in compliance with the inventory
PICCS		:	On the inventory,	or in compliance with the inventory
IECSC		:	On the inventory,	or in compliance with the inventory
NZIoC		:	On the inventory,	or in compliance with the inventory
TECI		:	On the inventory,	or in compliance with the inventory

TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

MPK



- OSHA P0 / IWA : 8-nour time weighted average OSHA P0 / STEL : Short-term exposure limit
- OSHA Z-1 / TWA : 8-hour time weighted average

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to

MPK

50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods: vPvB - Very Persistent and Very Bioaccumulative

Revision Date

05/20/2022

·

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / Z8