

PRODUCT IDENTIFICATION



Product Name: 50% Vinegar - Concentrated Industrial Strength

CAS Number: 64-19-7

Molecular Formula: $C_2H_4O_2$

Molecular Weight: 60.05 g/mol

Grade: Technical

Purity / Concentration: 50%

Synonyms: Acetic Acid Solution, Industrial Vinegar

PRODUCT OVERVIEW

Alliance Chemical offers high-quality 50% Industrial Vinegar, a technical grade acetic acid solution designed for robust performance. This clear, colorless liquid is characterized by a precise 50.3% assay and low impurity profile, making it a reliable choice for diverse industrial applications.

Grade Significance: Technical grade indicates that this product is manufactured for industrial use where high consistency is required, but it does not meet the strict regulatory standards required for pharmaceutical or reagent-grade applications.

CERTIFICATE OF ANALYSIS — TYPICAL VALUES

PARAMETER	UNIT	TYPICAL	MIN	MAX	TEST METHOD
Assay (wt%)	%	50.3	49	51	Titration with NaOH
Color (APHA)	APHA	5	—	10	ASTM D1209
Specific Gravity (20°C)	g/mL	1.061	1.058	1.064	ASTM D4052
Residue After Ignition	%	0.0020	—	0.01	Gravimetric
Iron (Fe)	ppm	0.1	—	2	ICP-OES
Chloride (Cl ⁻)	ppm	0.2	—	5	Ion Chromatography
Sulfate (SO ₄ ²⁻)	ppm	0.5	—	10	Ion Chromatography

ND = Not Detected. Values are typical and may vary by lot.

PHYSICAL & CHEMICAL PROPERTIES

Appearance	Clear, colorless liquid	Odor	Pungent, vinegar-like odor
Form	Liquid	Boiling Point	Not characterized for the solution
Melting / Freezing Point	Not characterized for the solution	Flash Point	68–72
Solubility	Fully water soluble	Molecular Formula	$C_2H_4O_2$
Molecular Weight	60.05 g/mol	Vapor Pressure (20°C)	15 mmHg
Viscosity (25°C)	1.2 cP	Refractive Index (20°C)	1.373
Density (25°C)	1.05 g/mL		

APPLICATIONS

1. **Water Treatment** — This concentrated solution is effectively utilized to lower pH levels in water treatment systems to maintain chemical balance.
2. **Food Processing** — It serves as a critical food preservative and flavoring agent, helping to extend shelf life and enhance product profiles.
3. **Chemical Manufacturing** — The product acts as a versatile reactant in the synthesis of complex organic compounds for various industrial chemical processes.
4. **Industrial Cleaning** — Due to its acidic properties, it is highly effective at dissolving stubborn mineral deposits and stains from industrial equipment.

STORAGE & HANDLING

Proper storage is critical because this product is classified as a flammable liquid and can cause severe skin burns. It must be kept in a cool, well-ventilated area away from heat sources to mitigate the risk of fire and vapor accumulation.

- Store in a cool, dry place away from direct sunlight.
- Use containers made of HDPE or glass to prevent chemical reactions.
- Avoid contact with strong oxidizers and bases.
- Ensure proper ventilation in storage areas to prevent vapor accumulation.
- Wear appropriate personal protective equipment (PPE) when handling.

AVAILABLE PACKAGING

- 1 Quart
- 1 Gallon
- 5 Gallon
- 15 Gallon
- 55 Gallon
- 275 Gallon
- 330 Gallon

SAFETY SUMMARY (CROSS-REFERENCE TO SDS)

Signal Word: **Danger**



Hazard Statements:

- H226: Flammable liquid and vapor [Warning Flammable liquids]
- H314: Causes severe skin burns and eye damage [Danger Skin corrosion/irritation]

Emergency Contact: CHEMTEL - 800-255-3924 (24 Hours/Day, 7 Days/Week)

For complete safety information, refer to the Safety Data Sheet (SDS) for this product.

Alliance Chemical | 204 South Edmond St, Taylor, Texas 76574 | 512-365-6838 | www.alliancechemical.com

Disclaimer: The information contained herein is believed to be accurate and represents the best information currently available to us. However, Alliance Chemical makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.