

Safety Data Sheet

ALLIANCE CHEMICAL

Talc, Powder

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Talc, Powder

Synonyms/Generic Names: Hydrous magnesium silicate; Talcum; Talc
(Asbestos free and less than 1% crystalline silica)

Product Number: 4538

Product Use: Industrial, Manufacturing or Laboratory use

Manufacturer: Alliance Chemical
204 S. Edmond St.
Taylor, Texas 76574

For More Information Call: 512-365-6838 (Monday-Friday 8:00am - 3:30pm)

In Case of Emergency Call: CALL CHEMTEL (800) 255-3924

2. HAZARDS IDENTIFICATION

OSHA Hazards: Carcinogen, Target Organ Effect, Toxic by inhalation

Target Organs: Lungs

Signal Word: Warning

Pictograms:



GHS Classification:

Acute toxicity, Inhalation	Category 4
Skin irritation	Category 3
Specific target organ toxicity - single exposure	Category 3

GHS Label Elements, including precautionary statements:

Hazard Statements:

H316	Causes mild skin irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

Precautionary Statements:

P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
------	---

Potential Health Effects

Eyes	May cause eye irritation.
Inhalation	Toxic if inhaled. May cause respiratory tract irritation
Skin	May be harmful if absorbed through skin. Causes skin irritation.
Ingestion	May be harmful if swallowed.

NFPA Ratings

Health	1
Flammability	0
Reactivity	0
Specific hazard	Not Available

HMIS Ratings

Health	1
Fire	0
Reactivity	0
Personal	E

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight %	CAS #	EINECS# / ELINCS#	Formula	Molecular Weight
Hydrous Magnesium Silicate	>99	14807-96-6	238-877-9	N/A	N/A
Crystalline Silica	<0.1-1	14808-60-7	238-878-4	N/A	N/A

4. FIRST-AID MEASURES

Eyes	In case of eye contact, rinse with plenty of water and seek medical attention if necessary.
Inhalation	Move casualty to fresh air and keep at rest. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention if necessary.
Skin	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and wash using soap. Get medical attention if necessary.
Ingestion	Do Not Induce Vomiting! Never give anything by mouth to an unconscious person. If conscious, wash out mouth with water. Get medical attention if necessary.

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media	Product is not flammable. Use appropriate media for adjacent fire. Cool unopened containers with water.
Special protective equipment and precautions for firefighters	Wear self-contained, approved breathing apparatus and full protective clothing, including eye protection and boots.
Specific hazards arising from the chemical	Emits toxic fumes (magnesium oxide, silicon oxides) under fire conditions. (See also Stability and Reactivity section).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	See section 8 for recommendations on the use of personal protective equipment.
Environmental precautions	Prevent spillage from entering drains. Any release to the environment may be subject to federal/national or local reporting requirements.
Methods and materials for containment and cleaning up	Pick up and arrange disposal without creating dust. Sweep up and place in suitable, closed containers for disposal. Clean surfaces thoroughly with water to remove residual contamination. Dispose of all waste and cleanup materials in accordance with regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

See section 8 for recommendations on the use of personal protective equipment. Use with adequate ventilation. Wash thoroughly after using. Keep container closed when not in use. Avoid formation of dusts.

Conditions for safe storage, including any incompatibilities

Store in cool, dry well ventilated area. Keep away from incompatible materials (see section 10 for incompatibilities).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure controls:

Component	Exposure Limits	Basis	Entity
Hydrous Magnesium Silicate	2R	TLV	ACGIH
	20 mppcf	PEL	OSHA
	2 mg/m ³	REL	NIOSH
Silica	0.025 mg/m ³	TLV	ACGIH

R = measured as respirable fraction of the aerosol
*respirable fraction

TWA: Time Weighted Average over 8 hours of work.

TLV: Threshold Limit Value over 8 hours of work.

REL: Recommended Exposure Limit

PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit during x minutes.

IDLH: Immediately Dangerous to Life or Health

WEEL: Workplace Environmental Exposure Levels

CEIL: Ceiling

Personal Protection

Eyes	Wear chemical safety glasses or goggles.
Inhalation	Provide local exhaust, preferably mechanical. If exposure levels are excessive, use an approved respirator.
Skin	Wear nitrile or rubber gloves, apron or lab coat.
Other	Not Available

Other Recommendations

Provide eyewash stations, quick-drench showers and washing facilities accessible to areas of use and handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.)	White to grayish white powdered solid.
Odor	Odorless.
Odor threshold	Not Available
pH	Not Available
Melting point/freezing point	800°C (1472°F)
Initial boiling point and boiling range	Not Available
Flash point	Not Flammable
Evaporation rate	Not Available
Flammability (solid, gas)	Not Flammable
Upper/lower flammability or explosive limit	Not Explosive
Vapor pressure	Not Available
Vapor density	5.7 (Air = 1)
Density	2.5 - 2.8(Water = 1)
Solubility (ies)	Insoluble in cold water, hot water.
Partition coefficient: n-octanol/water	Not Available
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available

10. STABILITY AND REACTIVITY

Chemical Stability	Stable
Possibility of Hazardous Reactions	Will not occur.
Conditions to Avoid	Not Available
Incompatible Materials	Oxidizing agents.
Hazardous Decomposition Products	Magnesium oxide, silicon oxides.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Skin	Not Available
Eyes	Not Available
Respiratory	Not Available
Ingestion	Not Available

Carcinogenicity

IARC	3 - Group 3: Not classifiable as to its carcinogenicity to humans (hydrous magnesium silicate). 1 - Group 1: Carcinogenic to humans (silica).
ACGIH	A4: Not classifiable as a human carcinogen (hydrous magnesium silicate).
NTP	Known to be human carcinogen (silica).
OSHA	No components of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Signs & Symptoms of Exposure

Skin	Irritation.
Eyes	Irritation, redness, watering eyes, itchiness.
Respiratory	Irritation, coughing, wheezing.
Ingestion	Irritation, nausea, vomiting, diarrhea.

Chronic Toxicity	May cause damage to the following organs: lungs.
Teratogenicity	Not Available
Mutagenicity	Not Available
Embryotoxicity	Not Available
Specific Target Organ Toxicity	Inhalation - May cause respiratory irritation. - Lungs
Reproductive Toxicity	Not Available
Respiratory/Skin Sensitization	Not Available

12. ECOLOGICAL INFORMATION

Ecotoxicity

Aquatic Vertebrate	Not Available
Aquatic Invertebrate	Not Available
Terrestrial	Not Available

Persistence and Degradability	Not Available
Bioaccumulative Potential	Not Available
Mobility in Soil	Not Available
PBT and vPvB Assessment	Not Available
Other Adverse Effects	Not Available

13. DISPOSAL CONSIDERATIONS

Waste Residues	Users should review their operations in terms of the applicable federal/national or local regulations and consult with appropriate regulatory agencies if necessary before disposing of waste product container.
Product Containers	Users should review their operations in terms of the applicable federal/national or local regulations and consult with appropriate regulatory agencies if necessary before disposing of waste product container.

The information offered in section 13 is for the product as shipped. Use and/or alterations to the product may significantly change the characteristics of the material and alter the waste classification and proper disposal methods.

14. TRANSPORTATION INFORMATION

US DOT	Not Dangerous Goods
TDG	Not Dangerous Goods
IMDG	Not Dangerous Goods
Marine Pollutant	No
IATA/ICAO	Not Dangerous Goods

15. REGULATORY INFORMATION

TSCA Inventory Status	All ingredients are listed on the TSCA inventory.
DSCL (EEC)	All ingredients are listed on the DSCL inventory.
California Proposition 65	Listed: Hydrous magnesium silicate and silica.
SARA 302	Not Listed
SARA 304	Not Listed
SARA 311	Hydrous magnesium silicate and silica.
SARA 312	Hydrous magnesium silicate and silica.
SARA 313	Not Listed
WHMIS Canada	Not Listed

16. OTHER INFORMATION

Revision	Date
Revision 3	10/15/2020

Disclaimer: Alliance chemical believes that the information herein is factual but is not intended to be all inclusive. The information relates only to the specific material designated and does not relate to its use in combination with other materials or its use as to any particular process. Because safety standards and regulations are subject to change and because Alliance Chemical has no continuing control over the material, those handling, storing or using the material should satisfy themselves that they have current information regarding the particular way the material is handled, stored or used and that the same is done in accordance with federal, state and local law. ALLIANCE CHEMICAL MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING (WITHOUT LIMITATION) WARRANTIES WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN OR WITH RESPECT TO FITNESS FOR ANY PARTICULAR USE.