

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Aluminum Sulfate 50%

Synonyms: Liquid Alum, Dialuminum Trisulfate, Aluminum Sulfate

CAS Number: 10043-01-3

Grade/Purity: Technical Grade

Product Type: Salts

Product Use: Industrial, Manufacturing or Laboratory use

Manufacturer/Supplier: Alliance Chemical, 204 South Edmond St, Taylor, Texas 76574

Information: 512-365-6838 | www.alliancechemical.com

Emergency: CHEMTEL - 800-255-3924 (24 Hours/Day, 7 Days/Week)

2. HAZARDS IDENTIFICATION

Signal Word: Danger

GHS Pictograms:



Hazard Statements:

H290	May be corrosive to metals
H314	Causes severe skin burns and eye damage

Precautionary Statements:

P234	Keep only in original packaging.
P260	Do not breathe dust, fume, gas, mist, vapours or spray.
P261	Avoid breathing dust, fume, gas, mist, vapours or spray.
P264	Wash hands and face thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, and eye/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor.
P321	Specific treatment (see first-aid information on this label).
P363	Wash contaminated clothing before reuse.
P390	Absorb spillage to prevent material damage.
P391	Collect spillage.
P405	Store locked up.
P406	Store in a corrosion resistant container with a resistant inner liner.

P501	Dispose of contents and container in accordance with local, regional, national, and international regulations.
------	--

3. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	% MIN	% MAX	CAS #	EINECS# / ELINCS#	FORMULA	MOLECULAR WEIGHT
Aluminum Sulfate	50	50	10043-01-3	233-135-0	Al ₂ O ₁₂ S ₃	342.2 g/mol
Water	50	50	7732-18-5	231-791-2	H ₂ O	18.02 g/mol

4. FIRST-AID MEASURES

Eyes	Rinse with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do. Continue rinsing. Seek medical attention immediately.
Skin	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing. Wash with soap. Get medical attention immediately.
Inhalation	Move person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.
Ingestion	Do Not Induce Vomiting! Never give anything by mouth to an unconscious person. If conscious, wash out mouth with water. Get medical attention immediately.

5. FIRE-FIGHTING MEASURES

Suitable Media	Dry chemical, CO ₂ , water spray. Use water spray to cool containers.
Unsuitable Media	Do not use a solid water stream as it may scatter and spread fire.
Protective Equipment	Wear self-contained breathing apparatus and full protective clothing.
Combustion Products	May include carbon oxides and other toxic fumes. See Section 10.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use PPE as described in Section 8. Ensure adequate ventilation. Evacuate personnel to safe areas.
Environmental	Prevent leakage or spillage from entering drains, sewers, or waterways.
Containment & Cleanup	Absorb with inert material. Collect in appropriate waste container. Dispose per applicable regulations.

7. HANDLING AND STORAGE

Safe Handling	Use with adequate ventilation. Avoid contact with skin, eyes, and clothing. Wash thoroughly after handling. Keep container closed when not in use.
Safe Storage	Store in a cool, dry, well-ventilated area. Use corrosion-resistant containers. Keep away from incompatible materials (see Section 10). Keep containers tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use adequate ventilation. Provide eyewash stations and quick-drench showers accessible to areas of use.

Occupational Exposure Limits:

AGENCY	EXPOSURE LIMIT
OSHA PEL	2 mg/m ³ TWA (as Al, soluble compounds)
NIOSH REL	2 mg/m ³ TWA (as Al, soluble salts)

Eyes	Wear chemical safety goggles or face shield.
Skin	Wear chemical-resistant gloves and protective clothing.
Inhalation	For mist or aerosol applications (e.g., spray, atomization, pressure washing), use a NIOSH-approved half-face air-purifying respirator with combination acid gas / P100 cartridges. For dust exposure, an N95 or P100 particulate filter is acceptable. Ensure local exhaust ventilation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	White crystalline powder
Odor	Odorless
Median Particle Size	Not Available
Particle Size Distribution	Not Available
Particle Shape	Not Available
Surface Area	Not Available
Dustiness	Not Available
Hygroscopicity	Not Available
pH	1.4-2.4 (50% solution)
Melting Point	Not characterized for the 50% solution
Boiling Point	Not characterized for the 50% solution
Flash Point	Not flammable
Vapor Pressure	Essentially zero
Specific Gravity	1.33
Solubility	Highly water soluble
Molecular Formula	$\text{Al}_2\text{O}_{12}\text{S}_3$
Molecular Weight	342.2 g/mol

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended storage conditions.
Hazardous Reactions	None under normal processing conditions.
Conditions to Avoid	Heat, sparks, open flame, and incompatible materials.
Incompatible Materials	Strong acids, strong bases, reactive metals, water (for some concentrated forms).
Decomposition Products	May produce carbon oxides and other toxic fumes when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity: See Section 2 for GHS hazard classification.

IARC	Not listed as carcinogen.
NTP	Not listed as carcinogen.
OSHA	Not listed as carcinogen.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Algae ErC50: > 25 mg/L (22 h, Aphanizomenon flos-aquae (cyanobacteria; static)); Daphnia EC50: 6.57 mg/L (48 h, Asellus aquaticus (isopod crustacean; renewal); 72-h 4.37 mg/L)
Persistence	Aquatic toxicity strongly pH-dependent via aluminum speciation (free/hydrolyzed Al^{3+} most toxic); endpoints vary with test pH
Bioaccumulation	Not Available
Mobility in Soil	Not Available

13. DISPOSAL CONSIDERATIONS

Dispose of contents/container in accordance with applicable federal, state, and local regulations. Do not dispose of into drains or waterways.

14. TRANSPORT INFORMATION

US DOT	UN3264, Corrosive liquid, acidic, inorganic, n.o.s. (Aluminum sulfate solution), 8, PG III
IMDG	UN3264, Corrosive liquid, acidic, inorganic, n.o.s. (Aluminum sulfate solution), 8, PG III
IATA/ICAO	UN3264, Corrosive liquid, acidic, inorganic, n.o.s. (Aluminum sulfate solution), 8, PG III
Marine Pollutant	No

15. REGULATORY INFORMATION

TSCA Inventory	Listed.
SARA 313 (TRI)	Not listed.
California Prop 65	Not listed.
SARA 311/312	See Section 2 for hazard classifications.

Data retrieved as of — TSCA Inventory: 2026-08-02; SARA 313 (TRI): 2026-08-02; California Prop 65: 2026-08-02

16. OTHER INFORMATION

Revision Date: 08/25/2026

Disclaimer: The information provided in this Safety Data Sheet is correct to the best of our knowledge at the date of publication. It relates only to the specific product identified and does not relate to its use in combination with other materials. ALLIANCE CHEMICAL MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ALLIANCE CHEMICAL DOES NOT ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE ARISING FROM THE HANDLING, STORAGE, USE, OR DISPOSAL OF THIS PRODUCT.