

PRODUCT IDENTIFICATION



Product Name: Ammonium Bifluoride Flakes
CAS Number: 1341-49-7
Molecular Formula: F_2H_5N
Molecular Weight: 57.044 g/mol
Grade: Technical Grade
Purity / Concentration: Not Available
Synonyms: Ammonium Hydrogen Fluoride, Ammonium Fluoride

PRODUCT OVERVIEW

Ammonium Bifluoride Flakes (CAS 1341-49-7) is a high-purity Technical Grade chemical characterized by a 97.5% assay and minimal impurity levels, such as 5 ppm of iron. These white crystalline flakes serve as a versatile fluoride source widely utilized in industrial etching, cleaning, and chemical synthesis applications.

Grade Significance: Technical Grade indicates that this product is manufactured to provide a balance of high purity and cost-effectiveness, making it ideal for industrial processes where precise chemical performance is required.

CERTIFICATE OF ANALYSIS — TYPICAL VALUES

PARAMETER	UNIT	TYPICAL	MIN	MAX	TEST METHOD
Assay	%	100.0	99.5	100.5	Titration/Gravimetric
Water Karl Fischer	%	ND	0	0.1	Karl Fischer
Arsenic As	ppm	2.1	0	10	ICP-MS
Copper Cu	ppm	15	0	30	ICP-OES
Heavy Metals As Pb	ppm	5	0	10	ICP-MS (as Pb)
Iron	ppm	6	0	10	ICP
Lead Pb	ppm	2.5	0	5	ICP-MS
Nickel Ni	ppm	5	0	10	ICP-OES
Sulfate (SO_4^{2-})	%	ND	0	0.01	ICP-MS
Silica SiO_2	%	0.01	0	0.01	Gravimetric

ND = Not Detected. Values are typical and may vary by lot.

PHYSICAL & CHEMICAL PROPERTIES

Appearance	White crystalline flakes	Odor	Slightly pungent
Form	Solid	Boiling Point	463.1 °F at 760 mmHg (Decomposes at 446 °F) (USCG, 1999)
Melting / Freezing Point	258 °F (USCG, 1999)	Specific Gravity	1.5
Solubility	Highly soluble in water	Molecular Formula	F_2H_5N
Molecular Weight	57.044 g/mol	Density (25°C)	1.25 g/mL

APPLICATIONS

1. **Semiconductor Manufacturing** — Used as a critical etching agent for silicon wafers to ensure precision in microchip fabrication.
2. **Industrial Cleaning** — Effectively removes stubborn oxides from glass and metal surfaces, restoring clarity and structural integrity.
3. **Chemical Synthesis** — Functions as a reliable fluoride source for the production of various specialized fluorinated compounds.
4. **Water Treatment** — Utilized for precise pH adjustment in industrial water systems to maintain chemical balance.

STORAGE & HANDLING

Ammonium Bifluoride must be stored in a cool, dry, and well-ventilated area to prevent moisture absorption and degradation. Because this material is toxic if swallowed and causes severe skin burns, it must be kept in tightly sealed, corrosion-resistant containers to prevent accidental exposure.

- Store in a cool, dry place away from moisture.
- Use appropriate personal protective equipment (PPE) such as gloves and goggles.
- Avoid contact with strong acids and bases to prevent hazardous reactions.
- Ensure proper ventilation in storage areas to minimize inhalation risks.
- Compatible with HDPE and glass containers; avoid metal containers.

AVAILABLE PACKAGING

- 2 lbs.
- 5 Lbs.
- 44 Lbs.

SAFETY SUMMARY (CROSS-REFERENCE TO SDS)

Signal Word: **Danger**



Hazard Statements:

- H301: Toxic if swallowed [Danger Acute toxicity, oral]
- H314: Causes severe skin burns and eye damage [Danger Skin corrosion/irritation]

Emergency Contact: CHEMTEL - 800-255-3924 (24 Hours/Day, 7 Days/Week)

For complete safety information, refer to the Safety Data Sheet (SDS) for this product.

Alliance Chemical | 204 South Edmond St, Taylor, Texas 76574 | 512-365-6838 | www.alliancechemical.com

Disclaimer: The information contained herein is believed to be accurate and represents the best information currently available to us. However, Alliance Chemical makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.