

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Blendpro - Professional Paint Thinning Solution Technical Grade

Synonyms: propan-2-one

CAS Number: 67-64-1

Grade/Purity: Technical Grade

Product Type: Solvents

Product Use: Industrial, Manufacturing or Laboratory use

Manufacturer/Supplier: Alliance Chemical, 204 South Edmond St, Taylor, Texas 76574

Information: 512-365-6838 | www.alliancechemical.com

Emergency: CHEMTEL - 800-255-3924 (24 Hours/Day, 7 Days/Week)

2. HAZARDS IDENTIFICATION

Signal Word: Danger

GHS Pictograms:



Hazard Statements:

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Precautionary Statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, and lighting equipment.
P242	Use non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash hands and face thoroughly after handling.
P280	Wear protective gloves, protective clothing, and eye/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.
P337+P313	If eye irritation persists: Get medical advice or attention.
P370+P378	In case of fire: Use appropriate media to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.

P405	Store locked up.
P501	Dispose of contents and container in accordance with local, regional, national, and international regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	% MIN	% MAX	CAS #	EINECS# / ELINCS#	FORMULA	MOLECULAR WEIGHT
Acetone	Technical grade (see specification)	Technical grade (see specification)	67-64-1	200-662-2	C ₃ H ₆ O	58.08 g/mol
Water	Balance		7732-18-5	231-791-2	H ₂ O	18.02 g/mol

4. FIRST-AID MEASURES

Eyes	EYES: First check the victim for contact lenses and remove if present. Flush victim's eyes with water or normal saline solution for 20 to 30 minutes while simultaneously calling a hospital or poison control center. Do not put any ointments, oils, or medication in the victim's eyes without specific instructions from a physician. IMMEDIATELY transport the victim after flushing eyes to a hospital even if no symptoms (such as redness or irritation) develop.
Skin	Remove contaminated clothes. Rinse skin with plenty of water or shower.
Inhalation	INHALATION: IMMEDIATELY leave the contaminated area; take deep breaths of fresh air. If symptoms (such as wheezing, coughing, shortness of breath, or burning in the mouth, throat, or chest) develop, call a physician and be prepared to transport the victim to a hospital. Provide proper respiratory protection to rescuers entering an unknown atmosphere. Whenever possible, Self-Contained Breathing Apparatus (SCBA) should be used; if not available, use a level of protection greater than or equal to that advised under Protective Clothing.
Ingestion	INGESTION: DO NOT INDUCE VOMITING. Volatile chemicals have a high risk of being aspirated into the victim's lungs during vomiting which increases the medical problems. If the victim is conscious and not convulsing, give 1 or 2 glasses of water to dilute the chemical and IMMEDIATELY call a hospital or poison control center. IMMEDIATELY transport the victim to a hospital. If the victim is convulsing or unconscious, do not give anything by mouth, ensure that the victim's airway is open and lay the victim on his/her side with the head lower than the body. DO NOT INDUCE VOMITING. IMMEDIATELY transport the victim to a hospital. (NTP, 1992)

5. FIRE-FIGHTING MEASURES

Suitable Media	Alcohol-resistant foam, CO ₂ , dry chemical powder. Water spray may be used to cool fire-exposed containers.
Unsuitable Media	Do not use a solid water stream — may scatter and spread fire.
Protective Equipment	Wear self-contained breathing apparatus and full protective clothing.
Combustion Products	May include carbon oxides and other toxic fumes. See Section 10.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use PPE as described in Section 8. Ensure adequate ventilation. Evacuate personnel to safe areas.
Environmental	Prevent leakage or spillage from entering drains, sewers, or waterways.
Containment & Cleanup	Absorb with inert material. Collect in appropriate waste container. Dispose per applicable regulations.

7. HANDLING AND STORAGE

Safe Handling	Use with adequate ventilation. Avoid contact with skin, eyes, and clothing. Wash thoroughly after handling. Keep container closed when not in use.
Safe Storage	Store in a cool, dry, well-ventilated area away from heat, sparks, and open flame. Keep away from incompatible materials (see Section 10). Keep containers tightly closed. Ground and bond containers when transferring material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use adequate ventilation. Provide eyewash stations and quick-drench showers accessible to areas of use.

Occupational Exposure Limits:

No established occupational exposure limits.

Eyes	Wear chemical safety goggles or face shield.
Skin	Wear chemical-resistant gloves and protective clothing.
Inhalation	Use a NIOSH-approved respirator with organic vapor cartridges. For confined spaces or exposures above the OEL, use supplied-air respiratory protection.

Exposure limits sourced from NIOSH Pocket Guide and OSHA 29 CFR 1910.1000. Hazard classification from ECHA Classification and Labelling Inventory (CLP Annex VI).

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Transparent light-weight solvent liquid
Odor	Solvent (acetone / ester / aromatic)
Particle Characteristics	Not Applicable
pH	Not Available
Melting Point	-95°C (-139°F)
Boiling Point	155°C (311°F)
Flash Point	40°C (104°F)
Vapor Pressure	Not Available
Specific Gravity	0.825
Solubility	High organic solvent compatibility
Molecular Formula	C ₃ H ₆ O
Molecular Weight	58.08 g/mol

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended storage conditions.
Hazardous Reactions	None under normal processing conditions.
Conditions to Avoid	Heat, sparks, open flame, and incompatible materials.
Incompatible Materials	Strong oxidizing agents, sources of ignition, heat.
Decomposition Products	May produce carbon oxides and other toxic fumes when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity: See Section 2 for GHS hazard classification.

IARC	Not listed as carcinogen.
NTP	Not listed as carcinogen.
OSHA	Not listed as carcinogen.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Daphnia EC50: 14852 mg/L (24 h, Artemia salina (brine shrimp; marine crustacean, not Daphnia); 24-h); Fish LC50: 5540 mg/L (96 h, Oncorhynchus mykiss (static; 95% CL 4740–6330))
Persistence	Not persistent in water — Readily biodegradable (96% ThBOD, MITI; aerobic + anaerobic)
Bioaccumulation	log Kow -0.24, BCF 3 (estimated; low)
Mobility in Soil	Very high mobility in soil (estimated Koc 2.4)

13. DISPOSAL CONSIDERATIONS

Dispose of contents/container in accordance with applicable federal, state, and local regulations. Do not dispose of into drains or waterways.

14. TRANSPORT INFORMATION

US DOT	UN1263, Paint related material including paint thinning, drying, removing, or reducing compound (Acetone, ethyl acetate, toluene), 3, PG II
IMDG	UN1263, Paint related material including paint thinning, drying, removing, or reducing compound (Acetone, ethyl acetate, toluene), 3, PG II
IATA/ICAO	UN1263, Paint related material including paint thinning, drying, removing, or reducing compound (Acetone, ethyl acetate, toluene), 3, PG II
Marine Pollutant	No

15. REGULATORY INFORMATION

TSCA Inventory	Listed.
SARA 313 (TRI)	Not listed.
California Prop 65	Not listed.
SARA 311/312	See Section 2 for hazard classifications.

Data retrieved as of — TSCA Inventory: 2026-08-02; SARA 313 (TRI): 2026-08-02; California Prop 65: 2026-08-02

16. OTHER INFORMATION

Revision Date: 08/09/2026

Disclaimer: The information provided in this Safety Data Sheet is correct to the best of our knowledge at the date of publication. It relates only to the specific product identified and does not relate to its use in combination with other materials. ALLIANCE CHEMICAL MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ALLIANCE CHEMICAL DOES NOT ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE ARISING FROM THE HANDLING, STORAGE, USE, OR DISPOSAL OF THIS PRODUCT.