

PRODUCT IDENTIFICATION

**Product Name:** Ethylene Glycol 60/40**CAS Number:** 107-21-1**Molecular Formula:** $C_2H_6O_2$ **Molecular Weight:** 62.07 g/mol**Grade:** Technical Grade**Purity / Concentration:** 60%**Synonyms:** Ethylene Glycol Solution, Ethylene Glycol Blend

PRODUCT OVERVIEW

Our Ethylene Glycol 60/40 is a high-quality technical grade aqueous solution designed for reliable thermal regulation. With a precise 61% assay and low impurity levels, such as 5 APHA color and minimal trace ions, it serves as an efficient heat transfer fluid and anti-freeze agent.

Grade Significance: Technical Grade indicates that this product is formulated for industrial and manufacturing utility rather than pharmaceutical or food-grade applications, providing a balance of cost-effectiveness and reliable performance.

CERTIFICATE OF ANALYSIS — TYPICAL VALUES

PARAMETER	UNIT	TYPICAL	MIN	MAX	TEST METHOD
Assay (wt%)	%	61	60	62	Titration with standardized NaOH
Color (APHA)	APHA	5	—	10	APHA/Hazen visual comparison
Specific Gravity (20°C)	g/mL	1.0625	1.06	1.065	Hydrometer or pycnometer at 20°C
Residue After Ignition	%	0.05	—	0.15	Gravimetric residue after ignition
Aluminum (Al)	ppm	0.1	—	0.5	ICP-OES
Arsenic (As)	ppm	0.02	—	0.1	ICP-MS
Calcium (Ca)	ppm	5	—	20	ICP-OES
Chromium (Cr)	ppm	0.1	—	0.5	ICP-OES
Cobalt (Co)	ppm	0.1	—	0.5	ICP-OES
Copper (Cu)	ppm	0.05	—	0.2	ICP-OES
Heavy Metals (as Pb)	ppm	0.05	—	0.2	ICP-OES
Iron (Fe)	ppm	0.1	—	0.5	ICP-OES
Lead (Pb)	ppm	0.05	—	0.2	ICP-OES
Magnesium (Mg)	ppm	5	—	20	ICP-OES
Manganese (Mn)	ppm	0.05	—	0.2	ICP-OES
Nickel (Ni)	ppm	0.05	—	0.2	ICP-OES
Potassium (K)	ppm	2	—	5	ICP-OES
Sodium (Na)	ppm	2	—	5	ICP-OES
Zinc (Zn)	ppm	0.2	—	0.5	ICP-OES
Ammonium (NH ₄ ⁺)	ppm	1	—	5	Ion chromatography
Chloride (Cl ⁻)	ppm	4	—	10	Ion chromatography (IC) or IC-ICP-OES
Nitrate (NO ₃ ⁻)	ppm	2	—	5	Ion chromatography
Phosphate (PO ₄ ³⁻)	ppm	1	—	5	Ion chromatography
Sulfate (SO ₄ ²⁻)	ppm	20	—	50	Ion chromatography

ND = Not Detected. Values are typical and may vary by lot.

PHYSICAL & CHEMICAL PROPERTIES

Appearance	Colorless, viscous liquid	Odor	Slightly sweet odor
Form	Liquid	Boiling Point	~110 °C
Melting / Freezing Point	-48 °C (freeze / crystallization onset)	Flash Point	Not flammable (aqueous solution)
Specific Gravity	1.08	Solubility	Soluble in water and alcohols
Molecular Formula	C ₂ H ₆ O ₂	Molecular Weight	62.07 g/mol
Vapor Pressure (20°C)	0.06 mmHg	Viscosity (25°C)	20.1 cP
Refractive Index (20°C)	1.431	Density (25°C)	1.115 g/mL

APPLICATIONS

1. **Automotive** — Used as a primary component in engine cooling systems to lower the freezing point and prevent overheating.
2. **Industrial Manufacturing** — Functions as a stable heat transfer medium in closed-loop industrial processes requiring consistent thermal management.
3. **Aviation** — Applied to aircraft surfaces during winter operations to effectively inhibit ice formation and ensure safety.
4. **Chemical Processing** — Utilized as a versatile solvent in various chemical synthesis applications where a controlled aqueous glycol environment is needed.

STORAGE & HANDLING

Proper storage in a cool, dry area is essential to maintain the integrity of the solution and prevent degradation. Because this product is harmful if swallowed and carries long-term health risks, it must be stored in clearly labeled, secure containers away from food and incompatible materials.

- Store in a cool, dry place away from direct sunlight.
- Use materials compatible with ethylene glycol, such as HDPE or stainless steel.
- Avoid contact with strong oxidizing agents.
- Ensure proper ventilation when handling to minimize inhalation exposure.
- Use personal protective equipment (PPE) such as gloves and goggles.

AVAILABLE PACKAGING

- 1 Quart
- 1 Gallon
- 5 Gallon
- 15 Gallon
- 55 Gallon
- 275 Gallon
- 330 Gallon

SAFETY SUMMARY (CROSS-REFERENCE TO SDS)

Signal Word: Warning



Hazard Statements:

- H302: Harmful if swallowed
- H373: May cause damage to organs through prolonged or repeated exposure

Emergency Contact: CHEMTEL - 800-255-3924 (24 Hours/Day, 7 Days/Week)

For complete safety information, refer to the Safety Data Sheet (SDS) for this product.

Alliance Chemical | 204 South Edmond St, Taylor, Texas 76574 | 512-365-6838 | www.alliancechemical.com

Disclaimer: The information contained herein is believed to be accurate and represents the best information currently available to us. However, Alliance Chemical makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.