

PRODUCT IDENTIFICATION

**Product Name:** Hydrogen Peroxide 15% ACS Grade**CAS Number:** 7722-84-1**Molecular Formula:** H_2O_2 **Molecular Weight:** 34.015 g/mol**Grade:** ACS Grade**Purity / Concentration:** 15%**Synonyms:** Hydrogen Peroxide Solution, H_2O_2 15%

PRODUCT OVERVIEW

Hydrogen Peroxide 15% ACS Grade is a high-purity, clear liquid oxidizing agent designed for precise laboratory and industrial applications. With a strictly controlled trace metal profile—including iron and heavy metals at 0.05 ppm—this solution ensures consistent performance in sensitive chemical reactions.

Grade Significance: ACS Grade signifies that this chemical meets the rigorous purity standards set by the American Chemical Society, ensuring it is suitable for use in demanding laboratory and analytical work.

CERTIFICATE OF ANALYSIS — TYPICAL VALUES

PARAMETER	UNIT	TYPICAL	MIN	MAX	TEST METHOD
Assay (Permanganate)	%	15.7	14.5	16	Permanganate Titration
Residue On Evaporation	ppm	10	0	20	Evaporation
Aluminum Al	ppm	0.5	0	1	ICP-MS
Arsenic Antimony As As	ppm	0.0050	0	0.01	ICP-MS
Calcium Ca	ppm	0.5	0	1	ICP-MS
Cobalt Co	ppm	0.25	0	0.5	ICP-MS
Copper	ppm	0.05	0	0.1	ICP
Iron	ppm	0.25	0	0.5	ICP
Lead Pb	ppm	0.25	0	0.5	ICP-MS
Magnesium Mg	ppm	0.05	0	0.1	ICP-MS
Manganese	ppm	0.5	0	1	ICP
Nickel Ni	ppm	0.05	0	0.1	ICP-MS
Potassium K	ppm	0.5	0	1	ICP-MS
Sodium Na	ppm	0.5	0	1	ICP-MS
Zinc Zn	ppm	0.5	0	1	ICP-MS
Chloride Cl	ppm	1	0	2	ICP
Phosphate Po4	ppm	1	0	2	ICP
Sulfate So4	ppm	3	0	5	ICP
Barium Ba	ppm	0.5	0	1	ICP-MS
Boron B	ppm	0.25	0	0.5	ICP-MS
Cadmium Cd	ppm	0.5	0	1	ICP-MS
Free Acid As H2So4	ueq/g	0.1	0	0.6	Titration
Silicon Si	ppm	0.5	0	1	ICP-MS
Silver Ag	ppm	0.25	0	0.5	ICP-MS
Strontium Sr	ppm	0.5	0	1	ICP-MS
Tin Sn	ppm	0.5	0	1	ICP-MS

ND = Not Detected. Values are typical and may vary by lot.

PHYSICAL & CHEMICAL PROPERTIES

Appearance	Colorless, clear liquid	Odor	Slightly sharp, pungent odor
Form	Liquid	Boiling Point	Not characterized for the 15% solution
Melting / Freezing Point	Not characterized for the 15% solution	Specific Gravity	1.05
Solubility	Soluble in water	Molecular Formula	H ₂ O ₂
Molecular Weight	34.015 g/mol	Vapor Pressure (20°C)	0.5 mmHg
Viscosity (25°C)	1.12 cP	Refractive Index (20°C)	1.406
Density (25°C)	1.11 g/mL		

APPLICATIONS

1. **Analytical Chemistry** — Used as a high-purity reagent in titrations and complex analytical procedures where low impurity levels are critical for accurate results.
2. **Textile and Paper** — Functions as a controlled bleaching agent to whiten fibers and pulp while maintaining material integrity.
3. **Environmental Services** — Employed in advanced wastewater treatment to effectively neutralize organic contaminants and remove odors through oxidation.
4. **Chemical Manufacturing** — Acts as a reliable oxidizing agent in various synthetic chemical reactions requiring a stable 15% concentration.

STORAGE & HANDLING

As a strong oxidizer, this product must be stored in a cool, ventilated area away from incompatible materials and direct sunlight to prevent decomposition. Improper storage can increase the risk of fire or pressure buildup, necessitating the use of vented containers to ensure safety.

- Store in a cool, dry place away from direct sunlight.
- Use containers made of HDPE or glass to prevent reactions.
- Avoid contact with organic materials and reducing agents.
- Ensure proper ventilation in storage areas to minimize vapor accumulation.
- Wear appropriate personal protective equipment (PPE) including gloves and goggles.

AVAILABLE PACKAGING

- 1 Quart
- 1 Gallon
- 5 Gallon
- 15 Gallon
- 55 Gallon
- 275 Gallon
- 330 Gallon

SAFETY SUMMARY (CROSS-REFERENCE TO SDS)

Signal Word: **Danger**



Hazard Statements:

- H271: May cause fire or explosion; strong Oxidizer [Danger Oxidizing liquids; Oxidizing solids]
- H302: Harmful if swallowed [Warning Acute toxicity, oral]
- H314: Causes severe skin burns and eye damage [Danger Skin corrosion/irritation]
- H332: Harmful if inhaled [Warning Acute toxicity, inhalation]

Emergency Contact: CHEMTEL - 800-255-3924 (24 Hours/Day, 7 Days/Week)

For complete safety information, refer to the Safety Data Sheet (SDS) for this product.

Alliance Chemical | 204 South Edmond St, Taylor, Texas 76574 | 512-365-6838 | www.alliancechemical.com

Disclaimer: The information contained herein is believed to be accurate and represents the best information currently available to us. However, Alliance Chemical makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.