

PRODUCT IDENTIFICATION



Product Name: Isobutyl Alcohol 99%
CAS Number: 78-83-1
Molecular Formula: C₄H₁₀O
Molecular Weight: 74.12 g/mol
Grade: Technical
Purity / Concentration: 99%
Synonyms: 2-Methyl-1-propanol, Isobutanol

PRODUCT OVERVIEW

Isobutyl Alcohol 99% is a high-purity technical grade solvent, also known as 2-Methyl-1-propanol, characterized by its clear, colorless appearance and low impurity profile. With a verified assay of 99.8% and minimal water content of 0.05%, this reagent is essential for industrial applications requiring consistent solvency and chemical stability.

Grade Significance: Technical grade indicates that the product is manufactured to meet rigorous industrial standards for purity and consistency, ensuring reliable performance in large-scale manufacturing and laboratory processes.

CERTIFICATE OF ANALYSIS — TYPICAL VALUES

PARAMETER	UNIT	TYPICAL	MIN	MAX	TEST METHOD
Assay (wt%)	%	99.8	99	—	GC
Color (APHA)	APHA	5	—	10	ASTM D1209
Specific Gravity (20°C)	g/mL	0.801	0.8	0.803	ASTM D4052
Residue After Evaporation	%	0.0005	—	0.0010	Gravimetric
Water Content	%	0.05	—	0.1	ASTM E203
Acidity As Acetic Acid	%	0.0010	—	0.0020	Titration
Carbonyl As C ₄ H ₈ O	%	0.0010	—	0.01	GC

ND = Not Detected. Values are typical and may vary by lot.

PHYSICAL & CHEMICAL PROPERTIES

Appearance	Clear, colorless liquid	Odor	Characteristic alcohol odor
Form	Liquid	Boiling Point	108°C (226.4°F)
Melting / Freezing Point	-108°C (-162.4°F)	Flash Point	28°C (82.4°F)
Solubility	Soluble in water, alcohol, and many organic solvents	Molecular Formula	C ₄ H ₁₀ O
Molecular Weight	74.12 g/mol	Vapor Pressure (20°C)	20 mmHg
Viscosity (25°C)	0.54 cP	Refractive Index (20°C)	1.396
Density (25°C)	0.803 g/mL	Decomposition Temp.	Not applicable under normal handling

APPLICATIONS

1. **Analytical Chemistry** — It functions as a reliable mobile phase component in reversed-phase high-performance liquid chromatography, facilitating the precise separation of complex organic compounds.
2. **Paints and Coatings** — The chemical is utilized as a high-performance solvent in paint formulations, providing excellent solvency properties that improve application consistency and finish quality.
3. **Chemical Manufacturing** — It serves as a critical intermediate for the synthesis of various esters and plasticizers, which are foundational components in plastics and industrial additives.
4. **Pharmaceuticals** — This solvent is employed in specialized extraction processes, helping manufacturers isolate active pharmaceutical ingredients with high purity requirements.

STORAGE & HANDLING

Due to its flash point of 28°C, Isobutyl Alcohol is classified as a flammable liquid and must be stored in a cool, well-ventilated area away from ignition sources. Proper containment prevents the accumulation of flammable vapors and ensures the integrity of the chemical by protecting it from moisture and contaminants.

- Store in a cool, well-ventilated area away from heat sources.
- Use containers made of HDPE or glass to prevent chemical reactions.
- Avoid contact with strong oxidizing agents and acids.
- Ensure proper personal protective equipment (PPE) is worn, including gloves and goggles.
- Keep away from direct sunlight to prevent degradation.

AVAILABLE PACKAGING

- 1 Quart
- 1 Gallon
- 5 Gallon
- 15 Gallon
- 55 Gallon
- 275 Gallon
- 330 Gallon

SAFETY SUMMARY (CROSS-REFERENCE TO SDS)

Signal Word: **Danger**



Hazard Statements:

- H226: Flammable liquid and vapor [Warning Flammable liquids]
- H315: Causes skin irritation [Warning Skin corrosion/irritation]
- H318: Causes serious eye damage [Danger Serious eye damage/eye irritation]
- H335: May cause respiratory irritation [Warning Specific target organ toxicity, single exposure; Respiratory tract irritation]
- H336: May cause drowsiness or dizziness [Warning Specific target organ toxicity, single exposure; Narcotic effects]

Emergency Contact: CHEMTEL - 800-255-3924 (24 Hours/Day, 7 Days/Week)

For complete safety information, refer to the Safety Data Sheet (SDS) for this product.

Alliance Chemical | 204 South Edmond St, Taylor, Texas 76574 | 512-365-6838 | www.alliancechemical.com

Disclaimer: The information contained herein is believed to be accurate and represents the best information currently available to us. However, Alliance Chemical makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.