

PRODUCT IDENTIFICATION

**Product Name:** Kerosene - K1 Clean Burning Fuel**CAS Number:** 8008-20-6**Molecular Formula:** $C_{10}H_{22}$ to $C_{16}H_{34}$ **Molecular Weight:** 142.28 g/mol**Grade:** Technical Grade**Purity / Concentration:** Not Available**Synonyms:** Kerosene Oil, Coal Oil

PRODUCT OVERVIEW

Alliance Chemical offers high-purity Kerosene (K1) as a versatile technical grade fuel and solvent. Featuring a high assay of 99.6% and exceptional clarity, this product is ideal for applications requiring consistent combustion and reliable performance.

Grade Significance: Technical grade indicates that this kerosene is manufactured for industrial and fuel-based applications where performance and cost-effectiveness are prioritized over pharmaceutical or food-grade purity standards.

CERTIFICATE OF ANALYSIS — TYPICAL VALUES

PARAMETER	UNIT	TYPICAL	MIN	MAX	TEST METHOD
Assay (wt%)	%	99.6	99	100.0	Distillation and mass balance with GC/summary (Titration not applicable); gravimetric analysis after distillation
Color (APHA)	APHA	2	—	5	APHA/Hazen visual comparison
Specific Gravity (20°C)	g/mL	0.81	0.79	0.82	Hydrometer or pycnometer at 20°C; ASTM D4052
Residue After Ignition	%	0.0050	—	0.01	Gravimetric residue after ignition following ASTM D482
Water Content	%	0.02	—	0.05	Karl Fischer titration
Aluminum (Al)	ppm	0.2	—	1	ICP-OES
Arsenic (As)	ppm	0.02	—	0.1	ICP-MS (ultra-trace metals)
Calcium (Ca)	ppm	1	—	5	IC or ICP-OES
Chromium (Cr)	ppm	0.1	—	0.5	ICP-OES
Cobalt (Co)	ppm	0.02	—	0.1	ICP-OES
Copper (Cu)	ppm	0.05	—	0.2	ICP-OES
Heavy Metals (as Pb)	ppm	0.05	—	0.5	ICP-MS
Iron (Fe)	ppm	0.05	—	0.5	ICP-OES
Lead (Pb)	ppm	0.05	—	0.2	ICP-OES
Magnesium (Mg)	ppm	1	—	5	ICP-OES
Manganese (Mn)	ppm	0.05	—	0.2	ICP-OES
Nickel (Ni)	ppm	0.05	—	0.2	ICP-OES
Potassium (K)	ppm	0.5	—	3	ICP-OES
Sodium (Na)	ppm	0.5	—	3	IC or ICP-OES
Zinc (Zn)	ppm	0.1	—	0.5	ICP-OES
Ammonium (NH ₄ ⁺)	ppm	1	—	5	Ion Chromatography (IC)
Chloride (Cl ⁻)	ppm	0.5	—	2	Ion Chromatography (IC) or IC-ICP-MS after sample digestion
Nitrate (NO ₃ ⁻)	ppm	1	—	5	Ion Chromatography (IC)
Phosphate (PO ₄ ³⁻)	ppm	1	—	5	Ion Chromatography (IC)
Sulfate (SO ₄ ²⁻)	ppm	2	—	10	Ion Chromatography (IC)

ND = Not Detected. Values are typical and may vary by lot.

PHYSICAL & CHEMICAL PROPERTIES

Appearance	Light amber liquid, transparent, low viscosity	Odor	Characteristic petroleum odor
Form	Liquid	Boiling Point	175°C (347°F)
Melting / Freezing Point	-40°C (-40°F)	Flash Point	48 °C (118.4 °F), Tag closed cup (ASTM D56)
Solubility	Low water solubility, dissolves in petroleum	Molecular Formula	C ₁₀ H ₂₂ to C ₁₆ H ₃₄
Molecular Weight	142.28 g/mol	Vapor Pressure (20°C)	0.5 mmHg
Viscosity (25°C)	1.5 cP	Refractive Index (20°C)	1.440
Density (25°C)	0.800 g/mL		

APPLICATIONS

1. **Residential Heating** — Acts as a primary, clean-burning heating fuel for residential space heaters and furnaces.
2. **Aviation** — Utilized as a specialized fuel source for various jet engine applications where high energy density is required.
3. **Industrial Cleaning** — Functions as a highly effective solvent for degreasing machinery and cleaning industrial equipment.
4. **Lighting** — Provides a steady, reliable fuel source for traditional oil lamps and emergency illumination devices.

STORAGE & HANDLING

Due to its flash point of 48°C, this kerosene is classified as a flammable liquid and must be stored in a cool, well-ventilated area away from open flames or sparks. Proper containment prevents the accumulation of flammable vapors, which is essential for maintaining a safe working environment.

- Store in a cool, well-ventilated area away from heat sources and open flames.
- Use containers made of HDPE or stainless steel to prevent chemical reactions.
- Avoid contact with strong oxidizing agents and acids.
- Ensure proper PPE, including gloves and goggles, are worn during handling.
- Regularly inspect storage containers for leaks or signs of degradation.

AVAILABLE PACKAGING

- 1 Quart
- 1 Gallon
- 5 Gallon
- 15 Gallon
- 55 Gallon
- 275 Gallon
- 330 Gallon

SAFETY SUMMARY (CROSS-REFERENCE TO SDS)

Signal Word: Warning



Hazard Statements:

- H226: Flammable liquid and vapor

Emergency Contact: CHEMTEL - 800-255-3924 (24 Hours/Day, 7 Days/Week)

For complete safety information, refer to the Safety Data Sheet (SDS) for this product.

Disclaimer: The information contained herein is believed to be accurate and represents the best information currently available to us. However, Alliance Chemical makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.