

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Methyl Isobutyl Ketone (MIBK) Technical Grade

Synonyms: Methyl Isobutyl Ketone (MIBK)

CAS Number: 108-10-1

Grade/Purity: Technical Grade

Product Type: Solvents

Product Use: Industrial, Manufacturing or Laboratory use

Manufacturer/Supplier: Alliance Chemical, 204 South Edmond St, Taylor, Texas 76574

Information: 512-365-6838 | www.alliancechemical.com

Emergency: CHEMTEL - 800-255-3924 (24 Hours/Day, 7 Days/Week)

2. HAZARDS IDENTIFICATION

Signal Word: Danger

GHS Pictograms:



Hazard Statements:

H225	Highly flammable liquid and vapour
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
EUH066	Repeated exposure may cause skin dryness or cracking

Precautionary Statements:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, and lighting equipment.
P242	Use non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust, fume, gas, mist, vapours or spray.
P261	Avoid breathing dust, fume, gas, mist, vapours or spray.
P264	Wash hands and face thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, and eye/face protection.
P281	Use personal protective equipment as required.

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice or attention.
P312	Call a POISON CENTER or doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice or attention.
P370+P378	In case of fire: Use appropriate media to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

3. COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	% MIN	% MAX	CAS #	EINECS# / ELINCS#	FORMULA	MOLECULAR WEIGHT
Methyl Isobutyl Ketone (MIBK)	99	100	108-10-1	203-550-1	C ₆ H ₁₂ O	100.16 g/mol

4. FIRST-AID MEASURES

Eyes	Rinse with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do. Continue rinsing. Seek medical attention immediately.
Skin	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing. Wash with soap. Get medical attention immediately.
Inhalation	Move person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention immediately.
Ingestion	Do Not Induce Vomiting! Never give anything by mouth to an unconscious person. If conscious, wash out mouth with water. Get medical attention immediately.

5. FIRE-FIGHTING MEASURES

Suitable Media	Alcohol-resistant foam, CO ₂ , dry chemical powder. Water spray may be used to cool fire-exposed containers.
Unsuitable Media	Do not use a solid water stream — may scatter and spread fire.
Protective Equipment	Wear self-contained breathing apparatus and full protective clothing.
Combustion Products	May include carbon oxides and other toxic fumes. See Section 10.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use PPE as described in Section 8. Ensure adequate ventilation. Evacuate personnel to safe areas.
Environmental	Prevent leakage or spillage from entering drains, sewers, or waterways.
Containment & Cleanup	Absorb with inert material. Collect in appropriate waste container. Dispose per applicable regulations.

7. HANDLING AND STORAGE

Safe Handling	Use with adequate ventilation. Avoid contact with skin, eyes, and clothing. Wash thoroughly after handling. Keep container closed when not in use.
Safe Storage	Store in a cool, dry, well-ventilated area away from heat, sparks, and open flame. Keep away from incompatible materials (see Section 10). Keep containers tightly closed. Ground and bond containers when transferring material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Use adequate ventilation. Provide eyewash stations and quick-drench showers accessible to areas of use.

Occupational Exposure Limits:

AGENCY	EXPOSURE LIMIT
OSHA PEL	100 ppm TWA
NIOSH REL	50 ppm TWA / 75 ppm STEL
IDLH	500 ppm

Eyes	Wear chemical safety goggles or face shield.
Skin	Wear chemical-resistant gloves and protective clothing.
Inhalation	Use a NIOSH-approved respirator with organic vapor cartridges. For confined spaces or exposures above the OEL, use supplied-air respiratory protection.

Exposure limits sourced from NIOSH Pocket Guide and OSHA 29 CFR 1910.1000. Hazard classification from ECHA Classification and Labelling Inventory (CLP Annex VI).

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Clear, colorless liquid
Odor	Characteristic
Median Particle Size	Not Applicable
Particle Size Distribution	Not Applicable
Particle Shape	Not Applicable
Surface Area	Not Applicable
Dustiness	Not Applicable
Hygroscopicity	Not Applicable
pH	Not Available
Melting Point	-120.5 °F (NTP, 1992)
Boiling Point	243 to 244 °F at 760 mmHg (NTP, 1992)
Flash Point	73 °F (NTP, 1992)
Vapor Pressure	Not Available
Specific Gravity	0.798
Solubility	Soluble in water, alcohol, ether, and most organic solvents
Molecular Formula	$C_6H_{12}O$
Molecular Weight	100.16 g/mol

10. STABILITY AND REACTIVITY

Chemical Stability	Stable under recommended storage conditions.
Hazardous Reactions	None under normal processing conditions.
Conditions to Avoid	Heat, sparks, open flame, and incompatible materials.
Incompatible Materials	Strong oxidizing agents, sources of ignition, heat.
Decomposition Products	May produce carbon oxides and other toxic fumes when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity: See Section 2 for GHS hazard classification.

IARC	Not listed as carcinogen.
NTP	Not listed as carcinogen.
OSHA	Not listed as carcinogen.

12. ECOLOGICAL INFORMATION

Ecotoxicity	Algae ErC50: 400 mg/L (96 h, Selenastrum capricornutum); Fish LC50: 505 mg/L (96 h, Pimephales promelas)
Persistence	Not persistent; volatilizes (air half-life ~30 d) — Readily biodegradable (84% ThBOD, MITI)
Bioaccumulation	log Kow 1.31, BCF 3 (estimated; low)
Mobility in Soil	High soil mobility (estimated Koc 70)

13. DISPOSAL CONSIDERATIONS

Dispose of contents/container in accordance with applicable federal, state, and local regulations. Do not dispose of into drains or waterways.

14. TRANSPORT INFORMATION

US DOT	UN1245, Methyl isobutyl ketone, 3, PG II
IMDG	UN1245, Methyl isobutyl ketone, 3, PG II
IATA/ICAO	UN1245, Methyl isobutyl ketone, 3, PG II
Marine Pollutant	No

15. REGULATORY INFORMATION

Regulatory listings not yet on file in this system; consult OSHA, EPA TSCA, EPCRA TRI, and California OEHHA directly.	
SARA 311/312	See Section 2 for hazard classifications.

16. OTHER INFORMATION

Revision Date: 07/22/2026

Disclaimer: The information provided in this Safety Data Sheet is correct to the best of our knowledge at the date of publication. It relates only to the specific product identified and does not relate to its use in combination with other materials. ALLIANCE CHEMICAL MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ALLIANCE CHEMICAL DOES NOT ASSUME LIABILITY FOR LOSS, INJURY, DAMAGE, OR EXPENSE ARISING FROM THE HANDLING, STORAGE, USE, OR DISPOSAL OF THIS PRODUCT.