

PRODUCT IDENTIFICATION



Product Name: Mineral Spirits - Odorless Solvent & Thinner Technical Grade

CAS Number: 64742-47-8

Molecular Formula: Primarily C₉-C₁₅ hydrocarbons

Molecular Weight: 134-170 g/mol

Grade: Technical Grade

Purity / Concentration: C9-C15 Cycloalkanes: 60-100% C9-C15 Alkanes: 15-40

Synonyms: Odorless Mineral Spirits, Paint Thinner

PRODUCT OVERVIEW

Our Odorless Mineral Spirits is a high-quality technical grade solvent composed of C9-C15 hydrocarbons. Featuring an aromatics content of just 0.3% and a flash point of at least 38 °C, this colorless liquid is the ideal choice for thinning oil-based paints and cleaning mechanical components.

Grade Significance: Technical grade indicates that this product is manufactured to meet consistent industrial standards for purity and performance, ensuring reliable results for professional applications.

CERTIFICATE OF ANALYSIS — TYPICAL VALUES

PARAMETER	UNIT	TYPICAL	MIN	MAX	TEST METHOD
Specific Gravity (20°C)	g/mL	0.76	0.758	0.762	Hydrometer @ 20°C
Aromatics	%	0.3	—	1	Per specification
Flash Point	°C	≥ 38 °C	—	—	Per specification

ND = Not Detected. Values are typical and may vary by lot.

PHYSICAL & CHEMICAL PROPERTIES

Appearance	Colorless liquid	Odor	Mild, characteristic solvent odor
Form	Liquid	Boiling Point	177-202 °C (352-396 °F), distillation range (ASTM D86)
Melting / Freezing Point	-58°C (-72.4°F)	Flash Point	60 °C (140 °F), Tag closed cup (ASTM D56)
Specific Gravity	0.8	Solubility	Very slightly soluble in water (1.5 g/L)
Molecular Formula	Primarily C ₉ -C ₁₅ hydrocarbons	Molecular Weight	134-170 g/mol
Vapor Pressure (20°C)	0.5 mmHg	Viscosity (25°C)	0.9 cP
Refractive Index (20°C)	1.460	Density (25°C)	0.790 g/mL
Decomposition Temp.	Note: Not normally subject to decomposition in normal use; decomposition not applicable		

APPLICATIONS

1. **Coatings and Paints** — This solvent is used to thin oil-based paints and varnishes, ensuring smoother application and better leveling on various surfaces.
2. **Maintenance and Repair** — It acts as an effective degreaser for cleaning brushes, tools, and mechanical parts contaminated with heavy grease or oil.
3. **Adhesives and Sealants** — The chemical serves as a reliable solvent base for the formulation and thinning of various industrial adhesives and sealants.
4. **Surface Preparation** — It is frequently used for cleaning surfaces prior to painting or coating to remove residues and ensure proper adhesion.

STORAGE & HANDLING

Due to its classification as a flammable liquid, this product must be stored in a cool, well-ventilated area away from heat sources and open flames. Proper containment prevents the accumulation of hazardous vapors and minimizes the risk of combustion during storage.

- Store in a cool, dry place away from heat sources and open flames.
- Use containers made of HDPE or glass to prevent chemical reactions.
- Ensure proper ventilation when using to minimize inhalation exposure.
- Avoid contact with strong oxidizing agents and acids.
- Wear appropriate personal protective equipment (PPE) such as gloves and goggles.

AVAILABLE PACKAGING

- 1 Quart
- 1 Gallon
- 5 Gallon
- 15 Gallon
- 55 Gallon

SAFETY SUMMARY (CROSS-REFERENCE TO SDS)

Signal Word: Warning



Hazard Statements:

- H226: Flammable liquid and vapor

Emergency Contact: CHEMTEL - 800-255-3924 (24 Hours/Day, 7 Days/Week)

For complete safety information, refer to the Safety Data Sheet (SDS) for this product.

Alliance Chemical | 204 South Edmond St, Taylor, Texas 76574 | 512-365-6838 | www.alliancechemical.com

Disclaimer: The information contained herein is believed to be accurate and represents the best information currently available to us. However, Alliance Chemical makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.