

PRODUCT IDENTIFICATION



Product Name: Sulfuric Acid 50% - Electrolyte Grade

CAS Number: 7664-93-9

Molecular Formula: H₂O₄S

Molecular Weight: 98.08 g/mol

Grade: Electrolyte

Purity / Concentration: 50%

Synonyms: Sulfuric Acid Dilute, Electrolyte Sulfuric Acid

PRODUCT OVERVIEW

Alliance Chemical offers high-purity Sulfuric Acid 50% in Electrolyte Grade, specifically formulated for sensitive electrochemical applications. This clear, viscous liquid features exceptionally low impurity levels, such as 0.1 ppm Iron and 0.05 ppm Heavy Metals, ensuring reliable performance in demanding industrial and laboratory environments.

Grade Significance: Electrolyte grade indicates a high-purity product with minimal metallic and ionic impurities, which is essential to prevent internal short-circuiting and premature degradation in electrochemical devices.

CERTIFICATE OF ANALYSIS — TYPICAL VALUES

PARAMETER	UNIT	TYPICAL	MIN	MAX	TEST METHOD
Assay (wt%)	%	50.3	49	51	Titration
Color (APHA)	APHA	5	—	10	ASTM D1209
Specific Gravity (20°C)	g/mL	1.395	—	—	ASTM D1298
Residue After Ignition	%	0.0005	—	0.0010	Gravimetric
Arsenic (As)	ppm	0.01	—	0.05	ICP-OES
Heavy Metals (as Pb)	ppm	0.05	—	1	ICP-OES
Iron (Fe)	ppm	0.1	—	0.2	ICP-OES
Chloride (Cl ⁻)	ppm	0.2	—	0.5	Ion Chromatography

ND = Not Detected. Values are typical and may vary by lot.

PHYSICAL & CHEMICAL PROPERTIES

Appearance	Clear, viscous liquid	Form	Liquid solution
Boiling Point	338°C (640°F)	Melting / Freezing Point	10°C (50°F)
Specific Gravity	1.403	Solubility	Complete water miscibility, organic solvent
Molecular Formula	H ₂ O ₄ S	Molecular Weight	98.08 g/mol

APPLICATIONS

1. **Battery Manufacturing** — Used as a high-purity electrolyte solution in lead-acid battery production to ensure optimal charge transfer and longevity.
2. **Laboratory Research** — Serves as a precise reagent for analytical chemistry and titration processes where trace metal contamination must be strictly controlled.
3. **Metal Finishing** — Utilized in electrolytic cleaning and pickling baths to remove surface impurities from precision metal components without introducing unwanted contaminants.
4. **Electronics** — Employed in semiconductor cleaning processes where the low residue profile is critical for maintaining component integrity.

STORAGE & HANDLING

Proper storage is vital because Sulfuric Acid is highly corrosive and can cause severe skin burns and eye damage upon contact. It must be kept in a cool, well-ventilated area in original, compatible containers to prevent dangerous reactions and ensure the long-term stability of the solution's precise concentration.

AVAILABLE PACKAGING

- 1 Quart
- 1 Gallon
- 5 Gallon
- 15 Gallon
- 55 Gallon
- 275 Gallon
- 330 Gallon

SAFETY SUMMARY (CROSS-REFERENCE TO SDS)

Signal Word: **Danger**



Hazard Statements:

- H314: Causes severe skin burns and eye damage [Danger Skin corrosion/irritation]

Emergency Contact: CHEMTEL - 800-255-3924 (24 Hours/Day, 7 Days/Week)

For complete safety information, refer to the Safety Data Sheet (SDS) for this product.

Alliance Chemical | 204 South Edmond St, Taylor, Texas 76574 | 512-365-6838 | www.alliancechemical.com

Disclaimer: The information contained herein is believed to be accurate and represents the best information currently available to us. However, Alliance Chemical makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.