

PRODUCT IDENTIFICATION



Product Name: Xylene
CAS Number: 1330-20-7
Molecular Formula: C₈H₁₀
Molecular Weight: 106.17 g/mol
Grade: Technical
Purity / Concentration: Not Available
Synonyms: Dimethylbenzene, Xylol

PRODUCT OVERVIEW

Xylene (CAS 1330-20-7) is a high-purity technical grade aromatic solvent characterized by its clear, volatile liquid form and 99.1% assay. With a low moisture content of 0.01% and minimal trace impurities, this chemical is essential for high-performance industrial applications requiring precise solvency.

Grade Significance: Technical grade Xylene offers a balance of high purity and cost-effectiveness, ensuring consistent performance for industrial processes where laboratory-grade refinement is not required.

CERTIFICATE OF ANALYSIS — TYPICAL VALUES

PARAMETER	UNIT	TYPICAL	MIN	MAX	TEST METHOD
Assay Gc Fid	%	100.0	99.5	100.5	GC-FID
Color (APHA)	APHA	≤ 20 APHA	—	—	ASTM D1209
Specific Gravity (20°C)	g/mL	0.8713	0.865	0.875	Hydrometer @ 25°C
Water Karl Fischer	ppm	13	—	100.0	ASTM E203
Chloride Cl	ppm	1	0	—	Ion Chromatography
Sulfate So4	ppm	1	0	1	Ion Chromatography
Distillation Range	°C	2.5	—	5	ASTM D1078
Nitrogen	ppm	0.5	—	1	Kjeldahl / Chemiluminescence

ND = Not Detected. Values are typical and may vary by lot.

PHYSICAL & CHEMICAL PROPERTIES

Appearance	Clear, colorless, volatile aromatic liquid	Odor	Sweet, aromatic odor
Form	Liquid	Boiling Point	138°C (280.4°F)
Melting / Freezing Point	-47°C (-52.6°F)	Flash Point	25°C (77°F)
Specific Gravity	0.865	Solubility	Low water solubility, excellent organic solvent
Molecular Formula	C ₈ H ₁₀	Molecular Weight	106.17 g/mol
Vapor Pressure (20°C)	6.7 mmHg	Viscosity (25°C)	0.89 cP
Refractive Index (20°C)	1.496	Density (25°C)	0.865 g/mL

APPLICATIONS

1. **Paints and Coatings** — Functions as a high-performance solvent that enhances the flow and leveling properties of industrial coatings.
2. **Chemical Manufacturing** — Acts as a vital chemical precursor for the synthesis of plastics, resins, and synthetic fibers.
3. **Pharmaceuticals** — Used as a specialized solvent for the extraction and purification of active pharmaceutical ingredients from organic plant materials.
4. **Analytical Chemistry** — Employed as a reliable solvent in high-performance liquid chromatography for the accurate separation of complex chemical compounds.

STORAGE & HANDLING

Proper storage is critical because Xylene is a flammable liquid with a flash point of 25°C, requiring a cool, well-ventilated area away from ignition sources to prevent vapor accumulation. Maintaining a sealed, airtight container prevents contamination and limits the risk of harmful inhalation or skin exposure.

- Store in a cool, well-ventilated area away from heat sources.
- Use containers made of HDPE or glass to prevent chemical reactions.
- Avoid contact with strong oxidizing agents and acids.
- Ensure proper PPE, including gloves and goggles, are worn during handling.
- Keep away from open flames and sources of ignition.

AVAILABLE PACKAGING

- 1 Quart
- 1 Gallon
- 5 Gallon
- 55 Gallon

SAFETY SUMMARY (CROSS-REFERENCE TO SDS)

Signal Word: **DANGER**



Hazard Statements:

- H226: Flammable liquid and vapor
- H319: Causes serious eye irritation
- H332: Harmful if inhaled

Emergency Contact: CHEMTEL - 800-255-3924 (24 Hours/Day, 7 Days/Week)

For complete safety information, refer to the Safety Data Sheet (SDS) for this product.

Alliance Chemical | 204 South Edmond St, Taylor, Texas 76574 | 512-365-6838 | www.alliancechemical.com

Disclaimer: The information contained herein is believed to be accurate and represents the best information currently available to us. However, Alliance Chemical makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.